

	Autocar Expert MY 2020 Medium Duty 4X2 Cl	
NGINE AND EQUIPMENT	STANDARD	OPTIONAL
ENGINE ASSY	B 6.7 '17, 200 HP / 2600RPM / 520 FT-LB, CUMMINS	B 6.7 '17, 220 HP / 2600RPM / 520 FT-LB, CUMMINS
		B 6.7 '17, 240 HP / 2600RPM / 560 FT-LB, CUMMINS
		B 6.7 '17, 260 HP / 2600RPM / 660 FT-LB, CUMMINS
		L9 '17, 260 HP / 2200RPM / 720 FT-LB, CUMMINS
		L9 '17, 270 HP / 2200RPM / 800 FT-LB, CUMMINS
		L9 '17, 350 HP / 2200RPM / 1000 FT-LB, CUMMINS
		L9 '17, 350 Hi HP / 2200RPM / 1150 FT-LB, CUMMINS
		L9 '17 300HP / 2200RPM / 860 LB-FT, CUMMINS
		L9 '17 330HP / 2200RPM / 1000 LB-FT, CUMMINS
		L9N '18 250 HP @ 730 FT-LB
		L9N '18 260 HP @ 660 FT-LB
		L9N '18 300 HP @ 860 FT-LB
MUFFLER SYSTEM (DIESEL)	LH VERTICAL SMA	RH HORIZONTAL SMA
AUFFLER SYSTEM (GAS)		LH VERTICAL CATALYST
		RH HOR CATALYST
JREA DELIVERY SYSTEM	RH FRAME MTD 5 GAL. CAPACITY	LH FRAME MTD 5 GAL. CAPACITY
KEA DELIVER I SISIEM	KII FRAME MID J GAL. CAFACII I	
		LH FRAME MTD 10 GAL. CAPACITY
		RH FRAME MTD 10 GAL. CAPACITY
		NO DEF TANK PROVIDED
AIR CLEANER	13" ONE STAGE	13" ONE STAGE WITH SAFETY ELEMENT
RADIATOR	1000 SQ. IN. 3 ROW HIGH CAPACITY, COPPER / BRASS	1000 SQ. IN. ALUMINUM
RADIATOR SHELL/HOOD BEZEL	NO RADIATOR GUARD	RADIATOR GUARD
AN & DRIVE-ENGINE	FAN CLUTCH, VISCOUS	2-SPEED FAN
COOLANT HOSES	SILICONE HOSES WITH STEEL TUBING	
RADIATOR COOLANT	EXTENDED LIFE COOLANT	
ENGINE BLOCK HEATER	NO ENGINE BLOCK HEATER PROVIDED	PHILLIPS 120V 1000 WATT
HEATER RECEPTICAL LOCATION-ENGINE		RECEPTACLE LOCATED AT CAB STEPS, RH SIDE
STARTING AID-GLOW PLUG	GRID HEATER	NO ELECTRIC STARTING AID PROVIDED
HEATER-ENGINE OIL PAN	NO OIL PAN HEATER PROVIDED	ZERO-START,120V-150W, OIL PAN HEATER
ENGINE IDLE SHUT DOWN	ENGINE IDLE SHUT DOWN ENABLED ( 5 MINUTES )	ENGINE IDLE SHUT DOWN DISABLED
BRAKE-ENGINE	NO ENGINE BRAKE PROVIDED	CUMMINS VGT EXHAUST BRAKE
EXHAUST PIPING	NO EXHAUST BLANKETS	EXHAUST BLANKETS
RANSMISSION AND EQUIPMENT	STANDARD	OPTIONAL
RANSMISSION	ALLISON 2500-SERIES, 6-SPEED	ALLISON 3000 SERIES,6-SPEED
TRANSMISSION GEARING	6-SPEED	ALLISON 3500 SERIES,6-SPEED
TRANSMISSION CONTROLS	ARENS PUSH BUTTON CONTROLS	ALLISON PUSHBUTTON CONTROLS
COOLER-TRANSMISSION OIL	OIL TO WATER TYPE	REMOTE MOUNTED TOC
	TRANSYND SYNTHETIC AUTO TRANS FLUID	REMOTE MOUNTED TOC
TRANSMISSION LUBRICANT		
DRIVESHAFT-MAIN	SPICER 1710HD HALF ROUND	
RANSMISSION SUPPORTS	NO TRANSMISSION SUPPORTS PROVIDED	TRANSMISSION REAR SUPPORT
TO-TRANSMISSION MOUNTED	NO TRANSMISSION MOUNTED PTO PROVIDED	PTO PREP - 2500 TRANSMISSION W/ REAR SUPPORT
		PTO PREP - 3000/3500 TRANSMISSION W/ REAR SUPPORT
		MUNCIE CS6B-A6705-S1SS
		MUNCIE CS24-A1010-H3BX
RANSMISSION BREATHER	NO REMOTE TRANSMISSION BREATHER	TRANSMISSION REMOTE BREATHER
RANSMISSION OIL FILL/CHECK	OIL FILL TUBE / DIPSTICK W/ LEVEL SENSOR	OIL FILL TUBE / DIPSTICK W / LEVEL SENSOR W / REMOTE BREATHER
RONT AXLE AND EQUIPMENT	STANDARD	OPTIONAL
RONT AXLE	DANA 1202W STEER AXLE, 12000 LB CAPACITY	
FRONT SUSPENSION	5500 LB FLATLEAF 12,500 GROUND CAPACITY	6,000 LB FLAT LEAF, 13,200K GND CAP
HOCK ABSORBERS-FRONT	DOUBLE ACTING SINGLE - HEAVY DUTY	
TEERING GEAR	INTEGRAL POWER STEERING W/O ASSIST RAM TAS65	DUAL INTEGRAL POWER STEERING TAS65
		INTEGRAL POWER STEERING W/O ASSIST RAM T100
		DUAL INTEGRAL POWER STEERING T100
OWED STEEDING DESERVOD	TWO OLLART DEMOTE MOUNTED	DOAL INTEGRAL FOWER STEERING 1100
OWER STEERING RESERVOIR	TWO QUART REMOTE MOUNTED	
	ABS 4S/4M W/PLC	ABS 4S/4M W/PLC AND ATC
RAKE CONTROL SYSTEM	AD5 +5/+W W/1 LC	ADS TS/THI W/LEC AND ATC



	Autocar Expert MY 2020 Medium Duty 4X2 Class	/ Standard and Optional Specifications
RAKES-FOUNDATION, FRONT AXLE	MERITOR 15x4 Q PLUS	MERITOR 16.5X5 QP
RAKE DRUM-FRONT	CAST IRON	
RAKE SLACK ADJUSTERS-FRONT AXLE	MERITOR AUTOMATIC	
UBS-FRONT	STEEL HUB PILOTED,285MM BOLT CIRCLE	
RONT AXLE LUBRICANT	STANDARD	SYNTHETIC, DANA SPICER EP75W90, OR EQUIV
UST SHIELDS - FRT BRAKES	NO FRONT BRAKE DUST SHIELDS PROVIDED	DUST SHIELDS - FRONT BRAKES
REAR AXLE AND EQUIPMENT	STANDARD	OPTIONAL
XLE MODEL	MERITOR RS24-160, SINGLE REDUCTION AXLE (6.14 : 1 RATIO)	DANA SPICER 21060S 21,000 LB CAPACITY (6.17 or 7.17 : 1 RATIO)
		DANA SPICER S21 - 170E SINGLE SPEED 21,000 LBS (6.17 or 7.17 : 1 RATIO)
		DANA SPICER 21065T TWO SPEED 21,000 LBS (6.17/8.42 or 7.17/9.77 : 1 RATIO)
EAR SUSPENSION	HENDRICKSON HTS 21,000 LBS	HAS - 210 AIR RIDE SUSPENSION
HOCK ABSORBERS-REAR	2 SHOCK ABSORBERS	FOR AIR SUSPENSION - OUTBOARD MOUNTED
		FOR AIR SUSPENSION - INBOARD MOUNTED
		NO SHOCK ABSORBERS REAR SUSP. PROVIDED
RAKE CONTROL SYSTEM	ABS 6S/4M W/PLC	ABS 65/4M W/ATC & PLC
BRAKES-FOUNDATION, REAR AXLE	MERITOR 15X4 Q PLUS	MERITOR 16.5X5 QP
	CAST IRON	MERITOR 10.3A3 QF
BRAKE DRUMS		
BRAKE SLACK ADJUSTERS-REAR AXLE	ARVIN MERITOR AUTOMATIC-SINGLE AXLE	
IUBS-REAR	IRON HUB, HP 10 STUD	
REAR AXLE LUBRICANT	STANDARD	SYNTHETIC
REAR DRIVE AXLE STOPS	REAR BUMPSTOPS REQUIRED	NO REAR BUMPSTOPS REQUIRED
REAR DRIVE AXLE ANTI-SPIN DEVICES	NO ANTI-SPIN DEVICES PROVIDED	SINGLE AXLE FULL LOCKING WHEEL DIFF.
TORQUE RODS	LONGITUDINAL ONLY - RUBBER BUSHED	LONGITUDINAL & TRANSVERSE - RUBBER BUSHED
VHEEL OIL SEALS-REAR	SCOTSEAL PLUS XL	
DUST SHIELDS - REAR BRAKES	NO REAR AXLE DUST SHIELDS PROVIDED	DUST SHIELDS - REAR BRAKES
CHASSIS AND EQUIPMENT	STANDARD	OPTIONAL
VHEELBASE	164 INCHES	132, 135, 136, 138, 141, 144, 147, 149 INCHES
	TOTINCTIED	152, 155, 156, 156, 111, 117, 119 Interies
		151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES
		151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES 181, 184, 186, 190, 193, 196 INCHES
		151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES 181, 184, 186, 190, 193, 196 INCHES 200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES
RAME RAILS		151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES 181, 184, 186, 190, 193, 196 INCHES
RAME RAILS	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM	151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES 181, 184, 186, 190, 193, 196 INCHES 200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES RANGE BY REQUEST
FRAME REINFORCEMENT INNER	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED	151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES 181, 184, 186, 190, 193, 196 INCHES 200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES RANGE BY REQUEST .25" LINER, STANDARD LENGTH
RAME REINFORCEMENT INNER RAME FASTENERS	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS	151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES 181, 184, 186, 190, 193, 196 INCHES 200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES RANGE BY REQUEST .25" LINER, STANDARD LENGTH FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING
RAME REINFORCEMENT INNER RAME FASTENERS BUMPER FRONT	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER	151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES 181, 184, 186, 190, 193, 196 INCHES 200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES RANGE BY REQUEST .25" LINER, STANDARD LENGTH
RAME REINFORCEMENT INNER RAME FASTENERS BUMPER FRONT TOW DEVICE(S)	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER	151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES 181, 184, 186, 190, 193, 196 INCHES 200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES RANGE BY REQUEST .25" LINER, STANDARD LENGTH FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING HEAVY DUTY
RAME REINFORCEMENT INNER RAME FASTENERS BUMPER FRONT TOW DEVICE(S) RAME-FRONT EXTENSION	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED	151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES 181, 184, 186, 190, 193, 196 INCHES 200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES RANGE BY REQUEST .25" LINER, STANDARD LENGTH FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING HEAVY DUTY HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.)
RAME REINFORCEMENT INNER RAME FASTENERS BUMPER FRONT OW DEVICE(S) RAME-FRONT EXTENSION RAME-REAR CUT-OFF	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED STRAIGHT	151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES 181, 184, 186, 190, 193, 196 INCHES 200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES RANGE BY REQUEST .25" LINER, STANDARD LENGTH FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING HEAVY DUTY
RAME REINFORCEMENT INNER RAME FASTENERS BUMPER FRONT COW DEVICE(S) RAME-FRONT EXTENSION RAME-REAR CUT-OFF RAME CROSSMEMBER-CENTER	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED STRAIGHT 7-PIECE STEEL CROSSMEMBERS	151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES 181, 184, 186, 190, 193, 196 INCHES 200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES RANGE BY REQUEST .25" LINER, STANDARD LENGTH FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING HEAVY DUTY HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.)
RAME REINFORCEMENT INNER RAME FASTENERS BUMPER FRONT COW DEVICE(S) RAME-FRONT EXTENSION RAME-REAR CUT-OFF RAME CROSSMEMBER-CENTER RAME CROSSMEMBER-OVERHANG	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED STRAIGHT 7-PIECE STEEL CROSSMEMBERS 7 PC STEEL CMBR ROS - IF REQUIRED	151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES 181, 184, 186, 190, 193, 196 INCHES 200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES RANGE BY REQUEST .25" LINER, STANDARD LENGTH FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING HEAVY DUTY HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.) NOTCH FOR SWEEPER BODY
RAME REINFORCEMENT INNER RAME FASTENERS BUMPER FRONT OW DEVICE(S) RAME-FRONT EXTENSION RAME-REAR CUT-OFF RAME CROSSMEMBER-CENTER RAME CROSSMEMBER-OVERHANG RAME CROSSMEMBER-OVERHANG RAME CROSSMEMBER-END CLOSING	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED STRAIGHT 7-PIECE STEEL CROSSMEMBERS	151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES 181, 184, 186, 190, 193, 196 INCHES 200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES RANGE BY REQUEST .25" LINER, STANDARD LENGTH FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING HEAVY DUTY HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.)
RAME REINFORCEMENT INNER RAME FASTENERS BUMPER FRONT OW DEVICE(S) RAME-FRONT EXTENSION RAME-REAR CUT-OFF RAME CROSSMEMBER-CENTER RAME CROSSMEMBER-OVERHANG RAME CROSSMEMBER-OVERHANG RAME CROSSMEMBER-END CLOSING MIR TANK MOUNTING	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED STRAIGHT 7-PIECE STEEL CROSSMEMBERS 7 PC STEEL CMBR ROS - IF REQUIRED NO FRAME END CLOSING X-MEMBER PROVIDED AS MANY TANKS IN RAIL AS POSSIBLE	151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES 181, 184, 186, 190, 193, 196 INCHES 200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES RANGE BY REQUEST .25" LINER, STANDARD LENGTH FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING HEAVY DUTY HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.) NOTCH FOR SWEEPER BODY STEEL
RAME REINFORCEMENT INNER RAME FASTENERS UMPER FRONT OW DEVICE(S) RAME-FRONT EXTENSION RAME-REAR CUT-OFF RAME CROSSMEMBER-CENTER RAME CROSSMEMBER-OVERHANG RAME CROSSMEMBER-OVERHANG IR TANK MOUNTING NEUMATIC SYSTEM (RAPID FILL)	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED STRAIGHT 7-PIECE STEEL CROSSMEMBERS 7 PC STEEL CMBR ROS - IF REQUIRED NO FRAME END CLOSING X-MEMBER PROVIDED AS MANY TANKS IN RAIL AS POSSIBLE STANDARD	151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES 181, 184, 186, 190, 193, 196 INCHES 200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES RANGE BY REQUEST .25" LINER, STANDARD LENGTH FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING HEAVY DUTY HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.) NOTCH FOR SWEEPER BODY
RAME REINFORCEMENT INNER RAME FASTENERS BUMPER FRONT 'OW DEVICE(S) RAME-FRONT EXTENSION RAME-REAR CUT-OFF RAME CROSSMEMBER-CENTER 'RAME CROSSMEMBER-OVERHANG RAME CROSSMEMBER-END CLOSING IR TANK MOUNTING <b>PNEUMATIC SYSTEM (RAPID FILL)</b> IR COMPRESSOR	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED STRAIGHT 7-PIECE STEEL CROSSMEMBERS 7 PC STEEL CMBR ROS - IF REQUIRED NO FRAME END CLOSING X-MEMBER PROVIDED AS MANY TANKS IN RAIL AS POSSIBLE <b>STANDARD</b> CUMMINS WABCO 18.7 CFM COMPRESSOR	151, 152, 155, 157, 158, 161, 160, 167, 170, 171, 174, 178 INCHES 181, 184, 186, 190, 193, 196 INCHES 200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES RANGE BY REQUEST .25" LINER, STANDARD LENGTH FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING HEAVY DUTY HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.) NOTCH FOR SWEEPER BODY STEEL OPTIONAL
RAME REINFORCEMENT INNER RAME FASTENERS SUMPER FRONT OW DEVICE(S) RAME-FRONT EXTENSION RAME-REAR CUT-OFF RAME CROSSMEMBER-CENTER RAME CROSSMEMBER-OVERHANG RAME CROSSMEMBER-END CLOSING IR TANK MOUNTING <b>NEUMATIC SYSTEM (RAPID FILL)</b> IR COMPRESSOR	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED STRAIGHT 7-PIECE STEEL CROSSMEMBERS 7 PC STEEL CMBR ROS - IF REQUIRED NO FRAME END CLOSING X-MEMBER PROVIDED AS MANY TANKS IN RAIL AS POSSIBLE STANDARD	<ul> <li>151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES</li> <li>181, 184, 186, 190, 193, 196 INCHES</li> <li>200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES</li> <li>RANGE BY REQUEST</li> <li>.25" LINER, STANDARD LENGTH</li> <li>FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING</li> <li>HEAVY DUTY</li> <li>HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.)</li> <li>NOTCH FOR SWEEPER BODY</li> <li>STEEL</li> <li>OPTIONAL</li> <li>PULL CORDS WITH DV/2 WET TANK DRAIN</li> </ul>
RAME REINFORCEMENT INNER RAME FASTENERS BUMPER FRONT 'OW DEVICE(S) RAME-FRONT EXTENSION RAME-REAR CUT-OFF RAME CROSSMEMBER-CENTER 'RAME CROSSMEMBER-OVERHANG RAME CROSSMEMBER-END CLOSING IR TANK MOUNTING <b>PNEUMATIC SYSTEM (RAPID FILL)</b> IR COMPRESSOR	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED STRAIGHT 7-PIECE STEEL CROSSMEMBERS 7 PC STEEL CMBR ROS - IF REQUIRED NO FRAME END CLOSING X-MEMBER PROVIDED AS MANY TANKS IN RAIL AS POSSIBLE <b>STANDARD</b> CUMMINS WABCO 18.7 CFM COMPRESSOR	<ul> <li>151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES</li> <li>181, 184, 186, 190, 193, 196 INCHES</li> <li>200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES</li> <li>RANGE BY REQUEST</li> <li>.25" LINER, STANDARD LENGTH</li> <li>FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING</li> <li>HEAVY DUTY</li> <li>HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.)</li> <li>NOTCH FOR SWEEPER BODY</li> <li>STEEL</li> <li>OPTIONAL</li> <li>PULL CORDS WITH DV/2 WET TANK DRAIN</li> <li>PULL CORDS WITH HEATED DV/2 WET TANK DRAIN</li> </ul>
RAME REINFORCEMENT INNER RAME FASTENERS BUMPER FRONT 'OW DEVICE(S) RAME-FRONT EXTENSION RAME-REAR CUT-OFF RAME CROSSMEMBER-CENTER 'RAME CROSSMEMBER-OVERHANG RAME CROSSMEMBER-END CLOSING IR TANK MOUNTING <b>PNEUMATIC SYSTEM (RAPID FILL)</b> IR COMPRESSOR	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED STRAIGHT 7-PIECE STEEL CROSSMEMBERS 7 PC STEEL CMBR ROS - IF REQUIRED NO FRAME END CLOSING X-MEMBER PROVIDED AS MANY TANKS IN RAIL AS POSSIBLE <b>STANDARD</b> CUMMINS WABCO 18.7 CFM COMPRESSOR	<ul> <li>151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES</li> <li>181, 184, 186, 190, 193, 196 INCHES</li> <li>200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES</li> <li>RANGE BY REQUEST</li> <li>.25" LINER, STANDARD LENGTH</li> <li>FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING</li> <li>HEAVY DUTY</li> <li>HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.)</li> <li>NOTCH FOR SWEEPER BODY</li> <li>STEEL</li> <li>OPTIONAL</li> <li>PULL CORDS WITH DV/2 WET TANK DRAIN</li> <li>PULL CORDS WITH HEATED DV/2 WET TANK DRAIN</li> <li>CENTRAL DRAIN MANIFOLD WITH DV/2 WET TANK DRAIN</li> </ul>
RAME REINFORCEMENT INNER RAME FASTENERS BUMPER FRONT 'OW DEVICE(S) 'RAME-FRONT EXTENSION 'RAME-REAR CUT-OFF 'RAME CROSSMEMBER-CENTER 'RAME CROSSMEMBER-OVERHANG 'RAME CROSSMEMBER-OVERHANG 'RAME CROSSMEMBER-END CLOSING IIR TANK MOUNTING 'NEUMATIC SYSTEM (RAPID FILL) IIR COMPRESSOR	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED STRAIGHT 7-PIECE STEEL CROSSMEMBERS 7 PC STEEL CMBR ROS - IF REQUIRED NO FRAME END CLOSING X-MEMBER PROVIDED AS MANY TANKS IN RAIL AS POSSIBLE <b>STANDARD</b> CUMMINS WABCO 18.7 CFM COMPRESSOR	<ul> <li>151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES</li> <li>181, 184, 186, 190, 193, 196 INCHES</li> <li>200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES</li> <li>RANGE BY REQUEST</li> <li>.25" LINER, STANDARD LENGTH</li> <li>FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING</li> <li>HEAVY DUTY</li> <li>HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.)</li> <li>NOTCH FOR SWEEPER BODY</li> <li>STEEL</li> <li>OPTIONAL</li> <li>PULL CORDS WITH DV/2 WET TANK DRAIN</li> <li>PULL CORDS WITH HEATED DV/2 WET TANK DRAIN</li> <li>CENTRAL DRAIN MANIFOLD WITH HEATED DV/2 WET TANK DRAIN</li> <li>CENTRAL DRAIN MANIFOLD WITH HEATED DV/2 WET TANK DRAIN</li> </ul>
RAME REINFORCEMENT INNER RAME FASTENERS SUMPER FRONT OW DEVICE(S) RAME-FRONT EXTENSION RAME-REAR CUT-OFF RAME CROSSMEMBER-CENTER RAME CROSSMEMBER-OVERHANG RAME CROSSMEMBER-END CLOSING IR TANK MOUNTING <b>NEUMATIC SYSTEM (RAPID FILL)</b> IR COMPRESSOR	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED STRAIGHT 7-PIECE STEEL CROSSMEMBERS 7 PC STEEL CMBR ROS - IF REQUIRED NO FRAME END CLOSING X-MEMBER PROVIDED AS MANY TANKS IN RAIL AS POSSIBLE <b>STANDARD</b> CUMMINS WABCO 18.7 CFM COMPRESSOR	<ul> <li>151, 152, 155, 157, 158, 161, 160, 167, 170, 171, 174, 178 INCHES</li> <li>181, 184, 186, 190, 193, 196 INCHES</li> <li>200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES</li> <li>RANGE BY REQUEST</li> <li>.25" LINER, STANDARD LENGTH</li> <li>FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING</li> <li>HEAVY DUTY</li> <li>HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.)</li> <li>NOTCH FOR SWEEPER BODY</li> <li>STEEL</li> <li>OPTIONAL</li> <li>PULL CORDS WITH DV/2 WET TANK DRAIN</li> <li>PULL CORDS WITH HEATED DV/2 WET TANK DRAIN</li> <li>CENTRAL DRAIN MANIFOLD WITH HEATED DV/2 WET TANK DRAIN</li> <li>CENTRAL DRAIN MANIFOLD WITH HEATED DV/2 WET TANK DRAIN</li> <li>DV/2 IN ALL TANKS (NON-HEATED)</li> </ul>
RAME REINFORCEMENT INNER RAME FASTENERS BUMPER FRONT 'OW DEVICE(S) 'RAME-FRONT EXTENSION 'RAME-REAR CUT-OFF 'RAME CROSSMEMBER-CENTER 'RAME CROSSMEMBER-OVERHANG 'RAME CROSSMEMBER-OVERHANG 'RAME CROSSMEMBER-END CLOSING AIR TANK MOUNTING 'NEUMATIC SYSTEM (RAPID FILL) AIR COMPRESSOR AIR RESER VOIR DRAIN SYSTEM	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED STRAIGHT 7-PIECE STEEL CROSSMEMBERS 7 PC STEEL CMBR ROS - IF REQUIRED NO FRAME END CLOSING X-MEMBER PROVIDED AS MANY TANKS IN RAIL AS POSSIBLE <b>STANDARD</b> CUMMINS WABCO 18.7 CFM COMPRESSOR PULL CORDS ALL TANKS	<ul> <li>151, 152, 155, 157, 158, 161, 160, 167, 170, 171, 174, 178 INCHES</li> <li>181, 184, 186, 190, 193, 196 INCHES</li> <li>200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES</li> <li>RANGE BY REQUEST</li> <li>.25" LINER, STANDARD LENGTH</li> <li>FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING</li> <li>HEAVY DUTY</li> <li>HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.)</li> <li>NOTCH FOR SWEEPER BODY</li> <li>STEEL</li> <li>OPTIONAL</li> <li>PULL CORDS WITH DV/2 WET TANK DRAIN</li> <li>PULL CORDS WITH HEATED DV/2 WET TANK DRAIN</li> <li>CENTRAL DRAIN MANIFOLD WITH HEATED DV/2 WET TANK DRAIN</li> <li>CENTRAL DRAIN MANIFOLD WITH HEATED DV/2 WET TANK DRAIN</li> <li>DV/2 IN ALL TANKS (NON-HEATED)</li> </ul>
RAME REINFORCEMENT INNER RAME FASTENERS BUMPER FRONT 'OW DEVICE(S) 'RAME-FRONT EXTENSION RAME-REAR CUT-OFF RAME CROSSMEMBER-CENTER RAME CROSSMEMBER-OVERHANG RAME CROSSMEMBER-OVERHANG RAME CROSSMEMBER-END CLOSING IR TANK MOUNTING 'NEUMATIC SYSTEM (RAPID FILL) IR COMPRESSOR IR RESERVOIR DRAIN SYSTEM	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED STRAIGHT 7-PIECE STEEL CROSSMEMBERS 7 PC STEEL CMBR ROS - IF REQUIRED NO FRAME END CLOSING X-MEMBER PROVIDED AS MANY TANKS IN RAIL AS POSSIBLE <b>STANDARD</b> CUMMINS WABCO 18.7 CFM COMPRESSOR	<ul> <li>151, 152, 155, 157, 158, 161, 160, 167, 170, 171, 174, 178 INCHES</li> <li>181, 184, 186, 190, 193, 196 INCHES</li> <li>200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES</li> <li>RANGE BY REQUEST</li> <li>.25" LINER, STANDARD LENGTH</li> <li>FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING</li> <li>HEAVY DUTY</li> <li>HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.)</li> <li>NOTCH FOR SWEEPER BODY</li> <li>STEEL</li> <li>OPTIONAL</li> <li>PULL CORDS WITH DV/2 WET TANK DRAIN</li> <li>PULL CORDS WITH HEATED DV/2 WET TANK DRAIN</li> <li>CENTRAL DRAIN MANIFOLD WITH HEATED DV/2 WET TANK DRAIN</li> <li>CENTRAL DRAIN MANIFOLD WITH HEATED DV/2 WET TANK DRAIN</li> <li>DV/2 IN ALL TANKS (NON-HEATED)</li> </ul>
RAME REINFORCEMENT INNER RAME FASTENERS BUMPER FRONT 'OW DEVICE(S) RAME-FRONT EXTENSION RAME-REAR CUT-OFF RAME CROSSMEMBER-CENTER RAME CROSSMEMBER-OVERHANG RAME CROSSMEMBER-OVERHANG RAME CROSSMEMBER-END CLOSING AIR TANK MOUNTING PNEUMATIC SYSTEM (RAPID FILL) AIR COMPRESSOR AIR RESERVOIR DRAIN SYSTEM	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED STRAIGHT 7-PIECE STEEL CROSSMEMBERS 7 PC STEEL CMBR ROS - IF REQUIRED NO FRAME END CLOSING X-MEMBER PROVIDED AS MANY TANKS IN RAIL AS POSSIBLE <b>STANDARD</b> CUMMINS WABCO 18.7 CFM COMPRESSOR PULL CORDS ALL TANKS	<ul> <li>151, 152, 155, 157, 158, 161, 160, 167, 170, 171, 174, 178 INCHES</li> <li>181, 184, 186, 190, 193, 196 INCHES</li> <li>200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES</li> <li>RANGE BY REQUEST</li> <li>.25" LINER, STANDARD LENGTH</li> <li>FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING</li> <li>HEAVY DUTY</li> <li>HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.)</li> <li>NOTCH FOR SWEEPER BODY</li> <li>STEEL</li> <li>OPTIONAL</li> <li>PULL CORDS WITH DV/2 WET TANK DRAIN</li> <li>PULL CORDS WITH HEATED DV/2 WET TANK DRAIN</li> <li>CENTRAL DRAIN MANIFOLD WITH HEATED DV/2 WET TANK DRAIN</li> <li>CENTRAL DRAIN MANIFOLD WITH HEATED DV/2 WET TANK DRAIN</li> <li>DV/2 IN ALL TANKS (NON-HEATED)</li> </ul>
RAME REINFORCEMENT INNER RAME FASTENERS BUMPER FRONT COW DEVICE(S) RAME-FRONT EXTENSION RAME-REAR CUT-OFF RAME CROSSMEMBER-CENTER	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM NO INNER FRAME REINFORCEMENT PROVIDED HUCK BOLTS STANDARD DUTY BUMPER TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED STRAIGHT 7-PIECE STEEL CROSSMEMBERS 7 PC STEEL CMBR ROS - IF REQUIRED NO FRAME END CLOSING X-MEMBER PROVIDED AS MANY TANKS IN RAIL AS POSSIBLE <b>STANDARD</b> CUMMINS WABCO 18.7 CFM COMPRESSOR PULL CORDS ALL TANKS STEEL TANKS FOR SINGLE AXLE	<ul> <li>151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES</li> <li>181, 184, 186, 190, 193, 196 INCHES</li> <li>200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES</li> <li>RANGE BY REQUEST</li> <li>.25" LINER, STANDARD LENGTH</li> <li>FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING</li> <li>HEAVY DUTY</li> <li>HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.)</li> <li>NOTCH FOR SWEEPER BODY</li> <li>STEEL</li> <li>OPTIONAL</li> <li>PULL CORDS WITH DV/2 WET TANK DRAIN</li> <li>PULL CORDS WITH HEATED DV/2 WET TANK DRAIN</li> <li>CENTRAL DRAIN MANIFOLD WITH HEATED DV/2 WET TANK DRAIN</li> <li>CENTRAL DRAIN MANIFOLD WITH HEATED DV/2 WET TANK DRAIN</li> </ul>



JEL SYSTEM	STANDARD	OPTIONAL
EL TANK-LEFT	TEMP. FUEL TANK	50 GAL RECT STEEL TANK, LH MOUNTED
		50 GAL ALUMINUM RECR TANK, LH MOUNTED
		75 GAL 26" DIA UNPAINTED ALUMINUM
		75 GAL 26" ROUND STEEL TANK
		100 GAL 26" DIA UNPAINTED ALUM
		100 GAL 26" DIA STEEL
		ALTERNATE FUEL ENGINE-NO LH TANK
		DELETE LHS FUEL TANK
UEL TANK-RIGHT	DELETE RHS FUEL TANK	50 GAL RECT STEEL TANK, RH MOUNTED
		50 GAL ALUMINUM RECT TANK, RH MOUNTED
		75 GAL 26" DIA UNPAINTED ALUMINUM
		75 GAL 26" DIA STEEL
		100 GAL 26" DIA UNPAINTED ALUM
		100 GAL 26" DIA STEEL
UEL TANK MOUNTING LHS	FUEL TANK MTD FWD LHS - STD (IF PROVIDED)	FUEL TANK MTD LHS OTHER THAN STD - SPECIFY
	TOLE IN WILL TWO END STD (II TROVIDED)	NO LH FUEL TANK POSITION
UELTANIK MOUNTING DUG	NO DU FUEL TANK DOUTION	
UELTANK MOUNTING RHS	NO RH FUEL TANK POSITION	FUEL TANK MTD FWD RHS - STD (IF PROVIDED)
		FUEL TANK MOUNTED RHS OTHER THAN STD - SPECIFY
UEL FILTER ENGINE MOUNTED	SPIN-ON, ENGINE MOUNTED	NATURAL GAS FUEL CLEANER
UEL FILTER CHASSIS MOUNTED	FLEETGUARD FS SERIES F / W SEPARATOR, PROBE & DASH LIGHT	FLEETGUARD FS SERIES F / W HEATER, SEPARATOR, PROBE & DASH LIGHT
		NO ADDITIONAL FUEL FILTER PROVIDED
UEL LINES	SAE J844 NYLON TUBING	STAINLESS STEEL FOR CNG OR LNG
IRES AND WHEELS	STANDARD	OPTIONAL
RE SIZE & LOAD RANGE - FRONT	11R22.5G	11R22.5H
		12R22.5H
		275/70R22.5J
		295/75R22.5G
/HEELS-DISC FRONT	22.5x8.25 STEEL HP, 6.18 INSET, 5HH	22.5x8.25 ALUMINUM HP, 5.79 INSET, ALCOA #883677 LV1 FINISH
	22.5X0.25 5 TEEL III , 0.16 INSET, 5111	22.5 x 8.25, ALUMINUM HP, 5.71 INSET, ACCURIDE
		22.5X9.00 ALUMINUM HP, 5.96 INSET, ALCOA #89U64
		22.5X9.00 ALUMINUM HP, 6.02 INSET, ACCURIDE (WEIGHT REDUCTION)
		22.5x9.0 STEEL HP, 6.38 INSET, 5HH
		22.5X9.0 STEEL, HP, 5.25 INSET, 5HH, ACCURIDE #29039
IRE SIZE & LOAD RANGE - REAR	11R22.5G	12R22.5H
		12R22.5J
		275/70R22.5J
		295/75R22.5G
		455/55R22.5M
HEELS-DISC REAR	22.5X8.25 STEEL, HP, 5HH	22.5X9.00 ALUMINUM HP, ACCURIDE (WEIGHT REDUCTION)
TIEBES-DISC KEAK	44.5A6.45 STEEL, III, JIIII	
		22.5X8.25 ALUMINUM HP, ALCOA #883677 LV1 FINISH
		22.5X14 ALUMINUM HP, ALCOA #840608 LV1 FINISH
		22.5X9 ALUMINUM HP, 5.96 INSET, ALCOA #89U64
		22.5 x 8.25, ALUMINUM HP, ACCURIDE
LECTRICAL SYSTEM	STANDARD	OPTIONAL
LECTRICAL SYSTEM	12V, NEGATIVE GROUND	VI IIVAAL
LTERNATOR	DELCO REMY 12V 130AMP 22SI	DELCO REMY 36SI 12V 160 AMP
	DELCO KENTI 12 V 150/ INII 2201	DELCO REMY 1503112 V 100 AMI DELCO REMY 160 AMP, 28SI PAD MTD W/REMOTE SENSE
		DELCO REMY 200 AMP, 28SI PAD MTD.
FARTING MOTOR	DENSO 12V STARTER W/OCP	DELCO REMY 12V 39 MT W/OCP
ATTERY	2 BATTERIES, 12V, 1500CCA	2 BATTERIES, 31 ECL, 12V, 1900CCA
		2 BATTERIES, 31 ECL, 12V, 2000CCA
ATTERY BOX	BATTERY BOX. 2 BATTERY CAPACITY	
	BATTERY BOX, 2 BATTERY CAPACITY NO BATTERY SHUT-OFF SWITCH PROVIDED	SHUTOFE W/ LOCKOUT & EMERGENCY ILIMPER STUDS
SATTERY SHUT-OFF SWITCH	NO BATTERY SHUT-OFF SWITCH PROVIDED	SHUTOFF W/ LOCKOUT & EMERGENCY JUMPER STUDS
BATTERY BOX BATTERY SHUT-OFF SWITCH WIRING, BODY INTERFACE BACKUP ALARM		SHUTOFF W/ LOCKOUT & EMERGENCY JUMPER STUDS RP 170 COMPLIANT ECCO RMS 917 WITH MOTION DETECTOR XXXX



		An ISO 9001:2000 Certified Comp.
	Autocar Expert MY 2020 Medium Duty 4X2 Class 7 Stan	ndard and Optional Specifications
		NO BACKUP ALARM PROVIDED
VINDSHIELD WIPERS	ELECTRIC INTERMITTENT WIPERS	
IORN	SINGLE ELECTRIC	
IORN-AIR	NO AIR HORN PROVIDED	TWIN MOUNTED UNDER CAB
IOKN-AIK	NO AIR HORN I ROVIDED	I WIN MOONTED UNDER CAD
JGHTING	STANDARD	OPTIONAL
AMPS-HEAD	RECTANGULAR SEALED BEAM	LED HEADLAMPS
AMPS-RUNNING	NO DAYTIME RUNNING LIGHTS PROVIDED	DAYTIME
AMPS-STOP-TAIL	NO TAIL OR BACK-UP LAMPS PROVIDED	DOT 4 INCANDESCENT TAIL (TURN/BRAKE/BACK-UP) LAMPS
		DOT 4 LED TAIL (TURN/BRAKE/BACK-UP) LAMPS
		DUAL LED TRUCKLITE MODEL 44
TOP-TAIL HARNESS	OMIT TAIL LAMPS, BB CONN @ EOF	STD TAIL LAMP WIRING
AMPS-TURN SIGNAL -FRONT	AMBER FRONT TURN SIGNALS	LED FRONT TURN SIGNALS
AMPS-MARKER	AMBER LED ROOF MARKERS	CLEARANCE (ROOF CORNER) LAMPS WIRED TO BATTERY SHUT OFF
		(LINK TO DISCONNECT SWITCH)
CAB AND EQUIPMENT	STANDARD SINGLE LEFT HAND DRIVE CAB	OPTIONAL DUAL DRIVE LH AND RH SIT
AD SHELL	SINGLE LEFT HAND DRIVE CAD	DUAL DRIVE LH AND RH SII SINGLE RIGHT HAND DRIVE CAB
CAB DOORS	STEEL DOORS W/DUAL POWER WINDOWS	
TEP-CAB ACCESS, CAB MOUNTED	DUAL SELF CLEANING CAB ENTRANCE STEPS	
CAB FLOOR	WEAR RESISTANT MAT WITH FOAM BACK	
CAB DASH	DARK GREY WRAP-AROUND, 2X OVERSIZED CUP HOLDERS	
VERHEAD CONSOLE	2X STORAGE BINS, CENTER MOUNTED RADIO SLEEVE	
AB MOUNTING	PROGRESSIVE RUBBER MOUNTS - FRONT COIL AND SHOCK ABS - REAR	
AB TILT MECHANISM-C.O.E.	HYDRAULIC TILT WITH OUTO ENGAGE SAFETY LATCH	
IIRRORS-DUAL WEST COAST	MIRROR, BLACK, MOTORIZED/HTD POLYCARBONATE HOUSING W/SQUARE	
IIKKOKS-DUAL WEST COAST	MIRROR, BEACK, MOTORIZED/HTD TOLTCARDONATE HOUSING W/SQUARE MOTORIZED/HTD CONVEX MIRROR	MIRROR, CHROME, HTD, REMOTE, W / LWR HTD CONVEX
IIRRORS-AUXILIARY	NO CONVEX AUX. MIRRORS PROVIDED	LOW MOUNT 8 CONVEX MIRROR BLACK POLYCARBONATE HOUSING
IIKKOKS-AUAILIAK I	NO CONVEX RUX. MIRRORS FROVIDED	HIGH MOUNT 8 CONVEX, CHROME
OWN VIEW MIRRORS	NO DOWN VIEW MIRRORS PROVIDED	SINGLE DOWN VIEW MIRROR, RH SIDE
Own view Mikkoks	NO DOWN VIEW WIRKOKS I KOVIDED	DUAL DOWN VIEW MIRRORS, ONE EACH SIDE
GRILLE	AUTOCAR GRILLE BLACK	CHROMED AUTOCAR GRILLE
JKILLE	AUTOCAR ORIELE BLACK	AUTOCAR GRILLE WITH REMOVABLE WINTERFRONT COVER
		AUTOCAR ORIELE WITH REMOVABLE WINTERFRONT COVER
CAB CLIMATE CONTROL SYSTEM	44,000 BTU FRESH AIR, HEATER AND AIR CONDITIONER, DIGITAL CLIMATE	AUTOCAR CHROME GRIELE WITH REMOVABLE WINTERFRONT COVER
	CONTROL	
TEERING COLUMN	ADJ. TILT AND TELESCOPIC STEERING COLUMN	DUAL ADJ. TILT AND TELESCOPIC STEERING COLUMNS
TEERING WHEEL	SINGLE DRIVE 16 INCH DIAMETER	SINGLE DRIVE 18 INCH DIAMETER
		DUAL DRIVE 16 INCH DIAMETER
		DUAL DRIVE 18 INCH DIAMETER
EAT-DRIVER	STANDARD MECHANICAL SUSPENSION WITH ADJ. DAMPENER	ISRI HT914 HIGH BACK, AIR RIDE W/ RH ARM REST AND LUMBAR
		SEARS SEAT W/ AIR RIDE SUSP, W/ AIR CONTROLLED LUMBAR SUPPORT
EAT-PASSENGER	STANDARD MECHANICAL SUSPENSION SEAT WITH ADJ. DAMPENER	ISRI HT914 HIGH BACK, AIR RIDE W/ LH ARM REST AND LUMBAR
		SEARS SEAT W/ AIR RIDE SUSP, W/ AIR CONTROLLED LUMBAR SUPPORT
ADDITIONAL SEAT - PASSENGER	NO THIRD MAN SEAT AND LAP BELT PROVIDED	THIRD MAN SEAT AND LAP BELT - CENTER MOUNTED
EAT COVERING	BLACK CONDURA PLUS® CLOTH FABRIC	
EAT BELT	THREE POINT RETRACTABLE	THREE POINT RETRACTABLE BRIGHT ORANGE COLOR
		3RD MAN SEAT AND LAP BELT -CENTER MOUNTED
UN VISORS	LEFT AND RIGHT SIDE	
ADIO	RADIO PREP IN OVERHEAD CONSOLE	AM/FM / CD STEREO. ROOF MTD
		AM/FM/WB/MP3/CD/USB/BLUETOOTH
	12V AND DASH MOUNTED CIGAR LIGHTER	
OWER PORT		
		2 DASH SWITCHES WIRED TO POWER
	NO ADDITIONAL ELEC. SWITCHES	2 DASH SWITCHES, WIRED TO POWER (2) DASH SWITCHES (1) WIRED TO POWER FOR ROOF REACON LIGHT
ADDITIONAL ELEC. SWITCHES	NO ADDITIONAL ELEC. SWITCHES	(2) DASH SWITCHES, (1) WIRED TO POWER FOR ROOF BEACON LIGHT
YOWER PORT ADDITIONAL ELEC. SWITCHES BRAKE VALVE & PEDAL		(2) DASH SWITCHES, (1) WIRED TO POWER FOR ROOF BEACON LIGHT FIREWALL MTD RH BRAKE PEDAL FOR RHD
ADDITIONAL ELEC. SWITCHES	NO ADDITIONAL ELEC. SWITCHES	(2) DASH SWITCHES, (1) WIRED TO POWER FOR ROOF BEACON LIGHT



		An ISO 9001-2000 Certified Company
	Autocar Expert MY 2020 Medium Duty 4X2 Class 7 Sta	andard and Optional Specifications
LAMPS-CAB INTERIOR	LED DOME LAMPS	FLEX MAP
KEY & LOCK SETS-IGN/DOORS	2 ADDITIONAL KEYS PER TRUCK (4 TOTAL)	4 ADDITIONAL KEYS PER TRUCK (6 TOTAL)
		KEYED ALIKE FLEET SET #1 (23112213)
DRIVER MONITORING SYSTEM	NO DRIVER CAM WIRING PREP OVERHEAD CONSOLE	DRIVER CAM WIRING PREP OVERHEAD CONSOLE
CAMERAS	NO CAMERAS OR PREP PROVIDED	3RD EYE CAMERA PREP (CAB ONLY)
TRUCK ELECTRICAL CONTROL MODULE	NO ELECTRONIC CONTROL MODULE	DIAGNOSTIC AND INFORMATION DISPLAY
VEHICLE MONITORING SYSTEM	NO GEOTAB TRUCK MONITOR OR PREP	GEOTAB TRUCK MONITOR PREP
		GEOTAB TRUCK MONITOR
PAINT	STANDARD	OPTIONAL
CAB PAINT TYPE	STANDARD WHITE	CAB FIRST COLOR OTHER THAN STD, NON METALLIC
		CAB FIRST COLOR, METALLIC
CHASSIS COLOR	BLACK P3036	CHASSIS COLOR OTHER THAN STD SPECIFY
BUMPER COLOR	BUMPER COLOR SAME AS CAB WHITE	PAINT SAME AS CAB, STEEL
DISC WHEEL OD DIM COLOD		BUMPER COLOR SAME AS CHASSIS
DISC WHEEL OR RIM COLOR	STEEL, E-COAT WHITE / ALUM-UNPAINTED	CUSTOM COLOR - SPECIFY (PRICE PER WHEEL) STEEL, E-COAT GREY/ ALUM-UNPAINTED
AXLE WHEELEND COLOR	SAME AS CHASSIS	STEEL, E-COAT ORE 17 ALOM-ON AINTED
BASIC WARRANTIES (INDUSTRY BEST)	STANDARD	OPTIONAL
CHASSIS WARRANTY	STANDARD WARRANTY	EXTENDED WARRANTY - 2 YEARS / 200K MILES
		EXTENDED WARRANTY - 3 YEARS / 300K MILES EXTENDED WARRANTY - 4 YEARS / 350K MILES
		EXTENDED WARRANTY - 5 YEARS / 400K MILES
ENGINE WARRANTY	CUMMINS STANDARD WARRANTY (2 YRS -ISL, 3 YRS ISB)	2017 B6.7 HD1 4YRS/200K MILES EXTENDED WARRANTY PP1 MATRIX #231132
		2017 B6.7 HD1 5YRS/150K MILES EXTENDED WARRANTY PP1 MATRIX #231132
		2017 B6.7 HD1 5YRS/250K MILES EXTENDED WARRANTY PP1 MATRIX #231132
		2017 B6.7 HD1 5YRS/300K MILES EXTENDED WARRANTY PP1 MATRIX #231132
		2017 L9 HD1 3YRS/100K MILES EXTENDED WARRANTY PP1 MATRIX #231157
		2017 L9 HD1 3YRS/150K MILES EXTENDED WARRANTY PP1 MATRIX #231157
		2017 L9 HD1 4YRS/200K MILES EXTENDED WARRANTY PP1 MATRIX #231157
		2017 L9 HD1 5YRS/150K MILES EXTENDED WARRANTY PP1 MATRIX #231157 2017 L9 HD1 5YRS/250K MILES EXTENDED WARRANTY PP1 MATRIX #231157
		2017 L9 HD1 5 TKS/250K MILES EXTENDED WARKANTY PP1 MATRIX #251157
		2018 L9N GE1 5 YRS/150K MILES EXTENDED WARRANTY PP1 MATRIX #334196
		2018 L9N GE1 5 YRS/200K MILES EXTENDED WARRANTY PP1 MATRIX #334196
CUMMINS AFTERTREATMENT	NO EXTENDED AFTERTEATMENT WARRANTY (2 YRS -ISL, 3 YRS ISB)	2017 B6.7 AT3 AFTERTREATMENT 5YRS/150K MILES EXT WARRANTY MATRIX #231345
		2017 B6.7 AT3 AFTERTREATMENT 4YRS/200K MILES EXT WARRANTY MATRIX #231345
		2017 B6.7 AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231345
		2017 B6.7 AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231345
		2017 L9 AT3 AFTERTREATMENT 3YRS/100K MILES EXT WARRANTY MATRIX #231545
		2017 L9 AT3 AFTERTREATMENT 3YRS/150K MILES EXT WARRANTY MATRIX #231545
		2017 L9 AT3 AFTERTREATMENT 4YRS/200K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/150K MILES EXT WARRANTY MATRIX #231545
		2017 L9 AT3 AFTERTREATMENT 51KS/150K MILES EXT WARRANT MATRIX #251545 2017 L9 AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231545
		2017 L9 AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231545
TRANSMISSION WARRANTY	ALLISON 3YR WARRANTY	ALLISON 5YR WARRANTY
VEHICLE RATINGS	STANDARD	
VEHICLE TARE WEIGHT, FRONT	7,941 lbs.	
VEHICLE TARE WEIGHT, REAR	3,777 lbs.	
GAWF	12000 LBS	
GAWR	21000 LBS	
GVWR	33000 LBS	
VOCATION		
APPLICATIONS	CONCRETE PUMPER, ASPHALT DISTRIBUTOR, SWEEPER, ROAD PATCHER,	REFUSE, CITY DELIVERY/BOX TRUCK, PAINT STRIPER, GEN UTILITY, CITY PUMP, ETC
BODY CAPACITY	5, 6, 7, 8, 9, 10, 11, 12, 13 YARD	



#### Autocar Expert MY 2020 Medium Duty 4X2 Class 7 Standard and Optional Specifications

CAB INSTRUMENTATION	CAB WARNING DEVICES
SPEEDOMETER	PARK BRAKE
TACHOMETER	HIGH BEAM
ENGINE OIL PRESSURE	TURN SIGNAL
COOLANT TEMPERATURE	LOW FUEL
TRANSMISSION OIL TEMPERATURE	LOW AIR
VOLTMETER	SEAT BELT
FUEL LEVEL	DPF
HOUR METER	HEST
DEF LEVEL	AIR RESTRICTION INDICATOR
PRIMARY (A) AIR PRESSURE	FILTER WITH WATER IN FUEL INDICATOR
SECONDARY (B) AIR PRESSURE	
ODOMETER	

#### **OPERATORS CONTROLS**

TRIPMETER

PARK BRAKE PUSH/PULL HEADLAMPS TURN SIGNAL COLUMN MOUNTED BRAKE PEDAL ACCELERATOR PEDAL TRANSMISSION GEAR SELLECTOR PUSH BUTTON

#### **OPTIONAL EQUIPMENT**

FIRE EXTINGUISHER DRY TYPE ABC 5LB. CAP MTD. IN CAB TRIANGLE FLARE KIT IN CAB ADDITIONAL INSTRUMENTATION AUTO NEUTRAL EXHAUST BRAKE METHANE DETECTION SYSTEM BATTERY SHUTOFF SWITCH WITH EMERGENCY JUMPER STUDS PTO CONTROL SWITCH DAYTIME RUNNING LAMPS

# AUTOCAR ACMD $^{\circ}$



GINE AND EQUIPMENT	STANDARD	OPTIONAL
VGINE ASSY	B 6.7 '17, 200 HP / 2600RPM / 520 FT-LB, CUMMINS	B 6.7 '17, 220 HP / 2600RPM / 520 FT-LB, CUMMINS
	·····, ·········, ····················	B 6.7 '17, 240 HP / 2600RPM / 560 FT-LB, CUMMINS
		B 6.7 '17, 260 HP / 2600RPM / 660 FT-LB, CUMMINS
		L9 '17, 260 HP / 2200RPM / 720 FT-LB, CUMMINS
		L9 '17, 270 HP / 2200RPM / 800 FT-LB, CUMMINS
		L9 '17, 350 HP / 2200RPM / 1000 FT-LB, CUMMINS
		L9 '17, 350 Hi HP / 2200RPM / 1150 FT-LB, CUMMINS
		L9 17, 500 Hi Hi / 2200RPM / 860 LB-FT, CUMMINS
		L9 '17 330HP / 2200RPM / 1000 LB-FT. CUMMINS
		L9 17 350H 7 2200H M 7 1000 LB-11, COMMINS
		L9N 18 250 HP @ 660 FT-LB
		L9N '18 300 HP @ 860 FT-LB
AUFFLER SYSTEM (DIESEL)	LH VERTICAL SMA	RH HORIZONTAL SMA
IUFFLER SYSTEM (GAS)		LH VERTICAL CATALYST
		RH HOR CATALYST
IREA DELIVERY SYSTEM	RH FRAME MTD 5 GAL. CAPACITY	LH FRAME MTD 5 GAL. CAPACITY
		LH FRAME MTD 10 GAL. CAPACITY
		RH FRAME MTD 10 GAL. CAPACITY
		NO DEF TANK PROVIDED
AIR CLEANER	13" ONE STAGE	13" ONE STAGE WITH SAFETY ELEMENT
RADIATOR	1000 SQ. IN. 3 ROW HIGH CAPACITY, COPPER / BRASS	1000 SQ. IN. ALUMINUM
RADIATOR SHELL/HOOD BEZEL	NO RADIATOR GUARD	RADIATOR GUARD
AN & DRIVE-ENGINE	FAN CLUTCH, VISCOUS	2-SPEED FAN
COOLANT HOSES	SILICONE HOSES WITH STEEL TUBING	
RADIATOR COOLANT	EXTENDED LIFE COOLANT	
ENGINE BLOCK HEATER	NO ENGINE BLOCK HEATER PROVIDED	PHILLIPS 120V 1000 WATT
HEATER RECEPTICAL LOCATION-ENGINE	NO BLOCK HEATER RECEPT. PROVIDED	RECEPTACLE LOCATED AT CAB STEPS, RH SIDE
STARTING AID-GLOW PLUG	GRID HEATER	NO ELECTRIC STARTING AID PROVIDED
IEATER-ENGINE OIL PAN	NO OIL PAN HEATER PROVIDED	ZERO-START,120V-150W, OIL PAN HEATER
ENGINE IDLE SHUT DOWN	ENGINE IDLE SHUT DOWN ENABLED ( 5 MINUTES )	ENGINE IDLE SHUT DOWN DISABLED
BRAKE-ENGINE	NO ENGINE BRAKE PROVIDED	CUMMINS VGT EXHAUST BRAKE
EXHAUST PIPING	NO EXHAUST BLANKETS	EXHAUST BLANKETS
RANSMISSION AND EQUIPMENT	STANDARD	OPTIONAL
RANSMISSION	ALLISON 3000 SERIES, 6-SPEED	ALLISON 3500 SERIES,6-SPEED
TRANSMISSION GEARING	6-SPEED	
TRANSMISSION CONTROLS	ALLISON PUSHBUTTON CONTROLS	
COOLER-TRANSMISSION OIL	OIL TO WATER TYPE	REMOTE MOUNTED TOC
RANSMISSION LUBRICANT	TRANSYND SYNTHETIC AUTO TRANS FLUID	
RIVESHAFT-MAIN	SPICER 1710HD HALF ROUND	
RANSMISSION SUPPORTS	NO TRANSMISSION SUPPORTS PROVIDED	TRANSMISSION REAR SUPPORT
TO-TRANSMISSION MOUNTED	NO TRANSMISSION MOUNTED PTO PROVIDED	PTO PREP - 3000/3500 TRANSMISSION W/ REAR SUPPORT
		MUNCIE CS6B-A6705-S1SS
		MUNCIE CS24-A1010-H3BX
RANSMISSION BREATHER	NO REMOTE TRANSMISSION BREATHER	TRANSMISSION REMOTE BREATHER
RANSMISSION OIL FILL/CHECK	OIL FILL TUBE / DIPSTICK W/ LEVEL SENSOR	OIL FILL TUBE / DIPSTICK W / LEVEL SENSOR W / REMOTE BREATHER
RONT AXLE AND EQUIPMENT	STANDARD	OPTIONAL
RONT AXLE	DANA 1202W STEER AXLE, 12000 LB CAPACITY	DANA E-1322-W, 13,200 LB CAPACITY
		DANA E-1462W STEER AXLE, 14600 LB CAPACITY
		MERITOR MFS-14 STEER AXLE, 14700# RATING XXXX
		MERITOR MFS-16 STEER AXLE, 16000# RATING
		MERITOR MFS-18 STEER AXLE, 18000# RATING
FRONT SUSPENSION	5500 LB FLATLEAF 12,500 GROUND CAPACITY	6000 LB FLATLEAF 13,200K GND CAP
		6500 LB FLATLEAF 14,500 GROUND CAPACITY
		7500 LB FLATLEAF 16,500 GROUND CAPACITY
		JUU LD FLATLEAF TUJUU UKUUND CAFACITT

BUMPER FRONT



	Autocar Expert MY 2020 Medium Duty 4X2 Class	s 8 Standard and Optional Specifications
SHOCK ABSORBERS-FRONT STEERING GEAR	DOUBLE ACTING SINGLE - HEAVY DUTY INTEGRAL POWER STEERING W/O ASSIST RAM TAS65	DUAL INTEGRAL POWER STEERING TAS65
		INTEGRAL POWER STEERING W/O ASSIST RAM T100 DUAL INTEGRAL POWER STEERING T100
		DUAL INTEGRAL POWER STEERING TAS85
OWED STEEDING DESERVOID	TWO OLIADT DEMOTE MOUNTED	DUAL INTEGRAL POWER STEERING TAS65
OWER STEERING RESERVOIR BRAKE CONTROL SYSTEM	TWO QUART REMOTE MOUNTED ABS 4S/4M W/PLC	FOUR QUART REMOTE MOUNTED ABS 4S/4M W/PLC AND ATC
BRAKES-FOUNDATION, FRONT AXLE	MERITOR 16.5X5 QP	MERITOR 16.5X6 QP
BRAKE DRUM-FRONT	CAST IRON	
BRAKE SLACK ADJUSTERS-FRONT AXLE		
HUBS-FRONT	STEEL HUB PILOTED,285MM BOLT CIRCLE	
HUB CAPS - FRONT AXLE	CR ZYTEL HUBCAP	
FRONT AXLE LUBRICANT DUST SHIELDS - FRT BRAKES	STANDARD NO FRONT BRAKE DUST SHIELDS PROVIDED	SYNTHETIC,DANA SPICER EP75W90,OR EQUIV DUST SHIELDS - FRONT BRAKES
JUST SHIELDS - FRT BRAKES	NO FROM BRAKE DUST SHIELDS FROMIDED	DUST SHIELDS - FRONT BRAKES
REAR AXLE AND EQUIPMENT	STANDARD	OPTIONAL
AXLE MODEL	MERITOR RS24-160, SINGLE REDUCTION AXLE (6.14 : 1 RATIO)	DANA SPICER 21060S 21,000 LB CAPACITY (6.17 or 7.17 : 1 RATIO)
		DANA SPICER S21 - 170E SINGLE SPEED 21,000 LBS (6.17 or 7.17 : 1 RATIO)
		DANA SPICER 21065T TWO SPEED 21,000 LBS (6.14/8.42 or 7.17/9.77 : 1 RATIO) DANA S23-170, SINGLE REDUCTION AXLE (6.14 or 7.17 : 1 RATIO)
		DANA 523-170, SINGLE REDUCTION AXLE (0.14 of 7.17 : 1 RATIO) DANA S23-190E SINGLE REDUCTION AXLE (0.14 of 7.17 : 1 RATIO)
		DANA SPICER 23082T TWO SPEED 23,000 LBS (6.17/8.40/739 or 5.43/840/739: 1 RATIO)
		MERITOR RS26-185, SINGLE REDUCTION AXLE (6.14 : 1 RATIO)
		DANA S30-190 WIDE TRACK AXLE, (30,000 LB CAPACITY) (6.14 or 7.17 : 1 RATIO)
REAR SUSPENSION	HENDRICKSON HTS 23,000 LBS	DANA S30-190, (30,000 LB CAPACITY) (6.14 or 7.17 : 1 RATIO) HENDRICKSON HTS 21,000 LBS
XEAR SUSTENSION	HENDRICKSON III'S 23,000 EBS	HENDRICKSON HTS 26,000 LBS
		HAS - 210 AIR RIDE SUSPENSION
		HAS - 230 AIR RIDE SUSPENSION
		HENDRICKSON PAX-EX 262, AIR RIDE, 26,000 LB CAPACITY
		REYCO 102CC 31000 LB GROUND CAPACITY
SHOCK ABSORBERS-REAR	2 SHOCK ABSORBERS	HENDRICKSON HTS 31,000 LBS FOR AIR SUSPENSION - OUTBOARD MOUNTED
SHOCK ADSORDERS-REAK	2 SHOCK ADSORDERS	FOR AIR SUSPENSION - OUTBOARD MOUNTED
		NO SHOCK ABSORBERS REAR SUSP. PROVIDED
BRAKE CONTROL SYSTEM	ABS 6S/4M W/PLC	ABS 6S/4M W/ATC & PLC
BRAKES-FOUNDATION, REAR AXLE	MERITOR 16.5X5 QP	MERITOR 16.5X6 QP
BRAKE DRUMS	CAST IRON	
3RAKE SLACK ADJUSTERS-REAR AXLE 1UBS-REAR	ARVIN MERITOR AUTOMATIC-SINGLE AXLE IRON HUB, HP 10 STUD	
REAR AXLE LUBRICANT	STANDARD	SYNTHETIC
REAR DRIVE AXLE STOPS	REAR BUMPSTOPS REQUIRED	NO REAR BUMPSTOPS REQUIRED
REAR DRIVE AXLE ANTI-SPIN DEVICES	NO ANTI-SPIN DEVICES PROVIDED	SINGLE AXLE FULL LOCKING WHEEL DIFF.
FORQUE RODS	LONGITUDINAL ONLY - RUBBER BUSHED	LONGITUDINAL & TRANSVERSE - RUBBER BUSHED
WHEEL OIL SEALS-REAR	SCOTSEAL PLUS XL NO REAR AXLE DUST SHIELDS PROVIDED	DUST SHIELDS DEAD DDAVES
DUST SHIELDS - REAR BRAKES	NO REAR AXLE DUST SHIELDS PROVIDED	DUST SHIELDS - REAR BRAKES
CHASSIS AND EQUIPMENT	STANDARD	OPTIONAL
VHEELBASE	164 INCHES	132, 135, 136, 138, 141, 144, 147, 149 INCHES
		151, 152, 155, 157, 158, 161, 166, 167, 170, 171, 174, 178 INCHES 181, 184, 186, 190, 193, 196 INCHES
		200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES
		RANGE BY REQUEST
FRAME RAILS	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM	
FRAME REINFORCEMENT INNER	NO INNER FRAME REINFORCEMENT PROVIDED	.25" LINER, STANDARD LENGTH
FRAME FASTENERS	HUCK BOLTS	FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING

STANDARD DUTY BUMPER

HEAVY DUTY



		An ISO 9001:2000 Certified Con
	Autocar Expert MY 2020 Medium Duty 4X2 Class 8	Standard and Optional Specifications
TOW DEVICE(S) FRAME-FRONT EXTENSION FRAME-REAR CUT-OFF	TWO TOW HOOKS INTEGRAL W/X-MEMBER NO FRONT FRAME EXTENSION PROVIDED STRAIGHT	HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.) NOTCH FOR SWEEPER BODY
FRAME CROSSMEMBER-CENTER FRAME CROSSMEMBER-OVERHANG	7-PIECE STEEL CROSSMEMBERS 7 PC STEEL CMBR ROS - IF REQUIRED	
FRAME CROSSMEMBER-END CLOSING AIR TANK MOUNTING	NO FRAME END CLOSING X-MEMBER PROVIDED AS MANY TANKS IN RAIL AS POSSIBLE	STEEL
PNEUMATIC SYSTEM (RAPID FILL)	STANDARD	OPTIONAL
AIR COMPRESSOR	CUMMINS WABCO 18.7 CFM COMPRESSOR	
AIR RESERVOIR DRAIN SYSTEM	PULL CORDS ALL TANKS	PULL CORDS WITH DV/2 WET TANK DRAIN PULL CORDS WITH HEATED DV/2 WET TANK DRAIN CENTRAL DRAIN MANIFOLD WITH DV/2 WET TANK DRAIN CENTRAL DRAIN MANIFOLD WITH HEATED DV/2 WET TANK DRAIN DV/2 IN ALL TANKS (NON-HEATED) CENTRAL DRAIN MANIFOLD W/HTD DV/2 WET TANK DRAIN/SCHRADER CHARGE PORT
AIR TANK-BRAKE	STEEL TANKS FOR SINGLE AXLE	
AIR LINES-MAIN, CHASSIS	SAE J844 NYLON TUBING	WARGO 1000 RUIG AR DRUFR WALL DEV CONGER CONDENCED (SERAD ATOD
AIR DRYER EMERGENCY AIR SYSTEM CHARGING	WABCO 1200 PLUS AIR DRYER NO EMERGENCY CHARGING SYSTEM	WABCO 1200 PLUS AIR DRYER W/HALDEX CONSEP CONDENSER/SEPARATOR SINGLE GLADHAND, FRONT BUMPER, WET TANK
FUEL SYSTEM	STANDARD	OPTIONAL
FUEL TANK-LEFT	TEMP. FUEL TANK	50 GAL RECT STEEL TANK, LH MOUNTED
FUEL TANK-RIGHT	DELETE RHS FUEL TANK	50 GAL ALUMINUM RECR TANK, LH MOUNTED 75 GAL 26" DIA UNPAINTED ALUMINUM 75 GAL 26" ROUND STEEL TANK 100 GAL 26" DIA UNPAINTED ALUM 100 GAL 26" DIA STEEL ALTERNATE FUEL ENGINE-NO LH TANK DELETE LHS FUEL TANK 50 GAL RECT STEEL TANK, RH MOUNTED 50 GAL ALUMINUM RECT TANK, RH MOUNTED 75 GAL 26" DIA UNPAINTED ALUMINUM 75 GAL 26" DIA UNPAINTED ALUM
UEL TANK MOUNTING LHS	FUEL TANK MTD FWD LHS - STD (IF PROVIDED)	100 GAL 26" DIA STEEL FUEL TANK MTD LHS OTHER THAN STD - SPECIFY NO LH FUEL TANK POSITION
FUELTANK MOUNTING RHS	NO RH FUEL TANK POSITION	FUEL TANK MTD FWD RHS - STD (IF PROVIDED) FUEL TANK MOUNTED RHS OTHER THAN STD - SPECIFY
FUEL FILTER ENGINE MOUNTED	SPIN-ON, ENGINE MOUNTED	NATURAL GAS FUEL CLEANER
UEL FILTER CHASSIS MOUNTED	FLEETGUARD FS SERIES F / W SEPARATOR, PROBE & DASH LIGHT	FLEETGUARD FS SERIES F / W HEATER, SEPARATOR, PROBE & DASH LIGHT NO ADDITIONAL FUEL FILTER PROVIDED
FUEL LINES	SAE J844 NYLON TUBING	STAINLESS STEEL FOR CNG OR LNG
TIRES AND WHEELS	STANDARD	OPTIONAL
FIRE SIZE & LOAD RANGE - FRONT	11R22.5G	12R22.5J 11R22.5H 12R22.5H 275/70R22.5J 295/75R22.5G 315/80R22.5L
WHEELS-DISC FRONT	22.5x8.25 STEEL HP, 6.18 INSET, 5HH	315/80R22.5M 22.5x8.25 ALUMINUM HP, 5.79 INSET, ALCOA #883677 LV1 FINISH 22.5 x 8.25, ALUMINUM HP, 5.71 INSET, ACCURIDE

22.5X9.00 ALUMINUM HP, 5.96 INSET, ALCOA #89U64

22.5x9.0 STEEL HP, 6.38 INSET, 5HH

22.5X9.00 ALUMINUM HP, 6.02 INSET, ACCURIDE (WEIGHT REDUCTION)



		An ISO 9001-2000 Certified Compa
	Autocar Expert MY 2020 Medium Duty 4X2 Class 8 Star	ndard and Optional Specifications
		22.5X9.0 STEEL, HP, 5.25 INSET, 5HH, ACCURIDE #29039
ΓIRE SIZE & LOAD RANGE - REAR	11R22.5G	11R22.5H
INE SIZE & LOAD IN INGE - REAK	11.22.50	12R22.5H
		12R22.5J
		275/70R22.5J
		295/75R22.5G
		315/80R22.5L
		315/80R22.5M
		455/55R22.5M
WHEELS-DISC REAR	22.5X8.25 STEEL, HP, 5HH	22.5X9.00 ALUMINUM HP, ACCURIDE (WEIGHT REDUCTION)
		22.5X9.0 STEEL, HP, 5HH
		22.5X8.25 ALUMINUM HP, ALCOA #883677 LV1 FINISH
		22.5X14 ALUMINUM HP, ALCOA #840608 LV1 FINISH
		22.5X9 ALUMINUM HP, 5.96 INSET, ALCOA #89U64
		22.5 x 8.25, ALUMINUM HP, ACCURIDE
ELECTRICAL SYSTEM ELECTRICAL SYSTEM	STANDARD 12V, NEGATIVE GROUND	OPTIONAL
ALTERNATOR	DELCO REMY 12V 130AMP 22SI	DELCO REMY 36SI 12V 160 AMP
	DESCONENT IET ISVINIT EEST	DELCO REMY 160 AMP, 28SI PAD MTD W/REMOTE SENSE
		DELCO REMY 100 AMP, 28SI FAD MID W/REMOTE SENSE DELCO REMY 200 AMP, 28SI PAD MTD.
STARTING MOTOR	DENSO 12V STARTER W/OCP	DELCO REMY 1200 AMP, 28SI FAD MTD. DELCO REMY 12V 39 MT W/OCP
BATTERY		2 BATTERIES, 31 ECL, 12V, 1900CCA
SATTERT	2 BATTERIES, 12V, 1500CCA	
		2 BATTERIES, 31 ECL, 12V, 2000CCA
BATTERY BOX	BATTERY BOX, 2 BATTERY CAPACITY	
BATTERY SHUT-OFF SWITCH	NO BATTERY SHUT-OFF SWITCH PROVIDED	SHUTOFF W/ LOCKOUT & EMERGENCY JUMPER STUDS
WIRING, BODY INTERFACE	NO BODY INTERFACE OPTION	RP 170 COMPLIANT
BACKUP ALARM	ECCO SMART ALARM SA917	ECCO RMS 917 WITH MOTION DETECTOR XXXX
		NO BACKUP ALARM PROVIDED
WINDSHIELD WIPERS	ELECTRIC INTERMITTENT WIPERS	
HORN	SINGLE ELECTRIC	
HORN-AIR	NO AIR HORN PROVIDED	TWIN MOUNTED UNDER CAB
LIGHTING	STANDARD	OPTIONAL
LAMPS-HEAD	RECTANGULAR SEALED BEAM	LED HEADLAMPS
LAMPS-RUNNING	NO DAYTIME RUNNING LIGHTS PROVIDED	DAYTIME
AMPS-STOP-TAIL	NO TAIL OR BACK-UP LAMPS PROVIDED	DOT 4 INCANDESCENT TAIL (TURN/BRAKE/BACK-UP) LAMPS
		DOT 4 LED TAIL (TURN/BRAKE/BACK-UP) LAMPS
		DUAL LED TRUCKLITE MODEL 44
TOP-TAIL HARNESS	OMIT TAIL LAMPS, BB CONN @ EOF	STD TAIL LAMP WIRING
AMPS-TURN SIGNAL -FRONT	AMBER FRONT TURN SIGNALS	LED FRONT TURN SIGNALS
AMPS-MARKER	AMBER LED ROOF MARKERS	CLEARANCE (ROOF CORNER) LAMPS WIRED TO BATTERY SHUT OFF
	AWIDER EED ROOF MARKERS	(LINK TO DISCONNECT SWITCH)
		OPTIONAL
CAB AND EQUIPMENT	STANDARD SINGLE LEFT HAND DRIVE CAB	OPTIONAL DUAL DRIVE LH AND RH SIT
	SINGLE LEI I HAND DRIVE CAD	SINGLE RIGHT HAND DRIVE CAB
CAB DOORS	STEEL DOORS W/DUAL POWER WINDOWS	
TEP-CAB ACCESS, CAB MOUNTED	DUAL SELF CLEANING CAB ENTRANCE STEPS	
CAB FLOOR	WEAR RESISTANT MAT WITH FOAM BACK	
CAB DASH	DARK GREY WRAP-AROUND, 2X OVERSIZED CUP HOLDERS	
VERHEAD CONSOLE	2X STORAGE BINS, CENTER MOUNTED RADIO SLEEVE	
AB MOUNTING	PROGRESSIVE RUBBER MOUNTS - FRONT COIL AND SHOCK ABS - REAR	
AB TILT MECHANISM-C.O.E.	HYDRAULIC TILT WITH OUTO ENGAGE SAFETY LATCH	
IIRRORS-DUAL WEST COAST	MIRROR, BLACK, MOTORIZED/HTD POLYCARBONATE HOUSING W/SQUARE	
	MOTORIZED/HTD CONVEX MIRROR	MIRROR, CHROME, HTD, REMOTE, W / LWR HTD CONVEX
MIRRORS-AUXILIARY	NO CONVEX AUX. MIRRORS PROVIDED	LOW MOUNT 8 CONVEX MIRROR BLACK POLYCARBONATE HOUSING
		HIGH MOUNT 8 CONVEX, CHROME



		An ISO 9001:2000 Cer
	Autocar Expert MY 2020 Medium Duty 4X2 Class 8 Sta	ndard and Optional Specifications
DOWN VIEW MIRRORS	NO DOWN VIEW MIRRORS PROVIDED	SINGLE DOWN VIEW MIRROR, RH SIDE
		DUAL DOWN VIEW MIRRORS, ONE EACH SIDE
GRILLE	AUTOCAR GRILLE BLACK	CHROMED AUTOCAR GRILLE
		AUTOCAR GRILLE WITH REMOVABLE WINTERFRONT COVER
		AUTOCAR CHROME GRILLE WITH REMOVABLE WINTERFRONT COVER
CAB CLIMATE CONTROL SYSTEM	44,000 BTU FRESH AIR, HEATER AND AIR CONDITIONER, DIGITAL CLIMATE	
	CONTROL	
STEERING COLUMN	ADJ. TILT AND TELESCOPIC STEERING COLUMN	DUAL ADJ. TILT AND TELESCOPIC STEERING COLUMNS
STEERING WHEEL	SINGLE DRIVE 16 INCH DIAMETER	SINGLE DRIVE 18 INCH DIAMETER
		DUAL DRIVE 16 INCH DIAMETER
		DUAL DRIVE 18 INCH DIAMETER
SEAT-DRIVER	STANDARD MECHANICAL SUSPENSION WITH ADJ. DAMPENER	ISRI HT914 HIGH BACK, AIR RIDE W/ RH ARM REST AND LUMBAR
		SEARS SEAT W/ AIR RIDE SUSP, W/ AIR CONTROLLED LUMBAR SUPPORT
SEAT-PASSENGER	STANDARD MECHANICAL SUSPENSION SEAT WITH ADJ. DAMPENER	ISRI HT914 HIGH BACK, AIR RIDE W/ LH ARM REST AND LUMBAR
		SEARS SEAT W/ AIR RIDE SUSP, W/ AIR CONTROLLED LUMBAR SUPPORT
ADDITIONAL SEAT - PASSENGER	NO THIRD MAN SEAT AND LAP BELT PROVIDED	THIRD MAN SEAT AND LAP BELT - CENTER MOUNTED
SEAT COVERING	BLACK CONDURA PLUS® CLOTH FABRIC	
SEAT BELT	THREE POINT RETRACTABLE	THREE POINT RETRACTABLE BRIGHT ORANGE COLOR
SUN VISORS	LEFT AND RIGHT SIDE	3RD MAN SEAT AND LAP BELT -CENTER MOUNTED
RADIO	RADIO PREP IN OVERHEAD CONSOLE	AM/FM / CD STEREO, ROOF MTD
KADIO	KADIO FREF IN OVERHEAD CONSOLE	AM/FM/CD STEREO, ROOF MID AM/FM/WB/MP3/CD/USB/BLUETOOTH
POWER PORT	12V AND DASH MOUNTED CIGAR LIGHTER	AM/FM/WB/MF5/CD/USB/BLUETOUTH
ADDITIONAL ELEC. SWITCHES	NO ADDITIONAL ELEC. SWITCHES	2 DASH SWITCHES, WIRED TO POWER
ADDITIONAL ELEC. SWITCHES	NO ADDITIONAL ELEC. SWITCHES	(2) DASH SWITCHES, (1) WIRED TO POWER FOR ROOF BEACON LIGHT
BRAKE VALVE & PEDAL	FIREWALL MTD LH BRAKE PEDAL FOR LHD	FIREWALL MTD RH BRAKE PEDAL FOR RHD
		FIREWALL MTD LHS, FLOOR MTD RH FOR DUAL DRIVE
PTO CONTROLS	NO TRANSMISSION PTO CONTROLS PROVIDED	PTO ELECTRIC CONTROL SWITCH
LAMPS-CAB INTERIOR	LED DOME LAMPS	FLEX MAP
KEY & LOCK SETS-IGN/DOORS	2 ADDITIONAL KEYS PER TRUCK (4 TOTAL)	4 ADDITIONAL KEYS PER TRUCK (6 TOTAL)
		KEYED ALIKE FLEET SET #1 (23112213)
DRIVER MONITORING SYSTEM	NO DRIVER CAM WIRING PREP OVERHEAD CONSOLE	DRIVER CAM WIRING PREP OVERHEAD CONSOLE
CAMERAS	NO CAMERAS OR PREP PROVIDED	3RD EYE CAMERA PREP (CAB ONLY)
TRUCK ELECTRICAL CONTROL MODULE	NO ELECTRONIC CONTROL MODULE	DIAGNOSTIC AND INFORMATION DISPLAY
VEHICLE MONITORING SYSTEM	NO GEOTAB TRUCK MONITOR OR PREP	GEOTAB TRUCK MONITOR PREP
		GEOTAB TRUCK MONITOR
PAINT	STANDARD	OPTIONAL
CAB PAINT TYPE	STANDARD WHITE	CAB FIRST COLOR OTHER THAN STD, NON METALLIC
CADIAINI IIIL	STANDARD WHITE	CAB FIRST COLOR, METALLIC
CHASSIS COLOR	BLACK P3036	CHASSIS COLOR OTHER THAN STD SPECIFY
BUMPER COLOR	BUMPER COLOR SAME AS CAB WHITE	PAINT SAME AS CAB, STEEL
		BUMPER COLOR SAME AS CHASSIS
DISC WHEEL OR RIM COLOR	STEEL, E-COAT WHITE / ALUM-UNPAINTED	CUSTOM COLOR - SPECIFY (PRICE PER WHEEL)
		STEEL, E-COAT GREY/ ALUM-UNPAINTED
AXLE WHEELEND COLOR	SAME AS CHASSIS	
BASIC WARRANTIES (INDUSTRY BEST)	STANDARD	OPTIONAL
CHASSIS WARRANTY	STANDARD WARRANTY	EXTENDED WARRANTY - 2 YEARS / 200K MILES
		EXTENDED WARRANTY - 3 YEARS / 300K MILES

ENGINE WARRANTY

CUMMINS STANDARD WARRANTY (2 YRS -ISL, 3 YRS ISB)

EXTENDED WARRANTY - 3 YEARS / 300K MILES EXTENDED WARRANTY - 4 YEARS / 350K MILES EXTENDED WARRANTY - 5 YEARS / 400K MILES 2017 B6.7 HD1 4YRS/200K MILES EXTENDED WARRANTY PP1 MATRIX #231132 2017 B6.7 HD1 5YRS/150K MILES EXTENDED WARRANTY PP1 MATRIX #231132 2017 B6.7 HD1 5YRS/250K MILES EXTENDED WARRANTY PP1 MATRIX #231132 2017 B6.7 HD1 5YRS/300K MILES EXTENDED WARRANTY PP1 MATRIX #231132 2017 L9 HD1 3YRS/100K MILES EXTENDED WARRANTY PP1 MATRIX #231157 2017 L9 HD1 3YRS/150K MILES EXTENDED WARRANTY PP1 MATRIX #231157



		An ISO 9001-2000 Certified Company
	Autocar Expert MY 2020 Medium Duty 4X2 Class 8 S	Standard and Optional Specifications
		2017 L9 HD1 4YRS/200K MILES EXTENDED WARRANTY PP1 MATRIX #231157 2017 L9 HD1 5YRS/150K MILES EXTENDED WARRANTY PP1 MATRIX #231157 2017 L9 HD1 5YRS/250K MILES EXTENDED WARRANTY PP1 MATRIX #231157 2017 L9 HD1 5YRS/300K MILES EXTENDED WARRANTY PP1 MATRIX #231157 2018 L9N GE1 5 YRS/150K MILES EXTENDED WARRANTY PP1 MATRIX #334196 2018 L9N GE1 5 YRS/200K MILES EXTENDED WARRANTY PP1 MATRIX #334196
CUMMINS AFTERTREATMENT	NO EXTENDED AFTERTEATMENT WARRANTY (2 YRS -ISL, 3 YRS ISB) ALLISON 3YR WARRANTY	2018 L5N GEL 5 TKS/200K MILES EATENDED WARRANT PPT MATRIX #334196 2017 B6.7 AT3 AFTERTREATMENT 5YRS/150K MILES EXT WARRANTY MATRIX #231345 2017 B6.7 AT3 AFTERTREATMENT 4YRS/200K MILES EXT WARRANTY MATRIX #231345 2017 B6.7 AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231345 2017 L9 AT3 AFTERTREATMENT 5YRS/100K MILES EXT WARRANTY MATRIX #231345 2017 L9 AT3 AFTERTREATMENT 3YRS/100K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 3YRS/100K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 3YRS/150K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 4YRS/200K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/150K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/150K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231545
VEHICLE RATINGS	STANDARD	OPTIONAL
VEHICLE TARE WEIGHT, FRONT	8.104 lbs.	01 HOMAL
VEHICLE TARE WEIGHT, REAR	3.847 lbs.	
GAWF	12000 LBS	13000 LBS
		14000 LBS
		16000 LBS
		18000 LBS
GAWR	23000 LBS	21000 LBS
		26000 LBS
		30000 LBS
GVWR	35000 LBS	34000 LBS
		36000 LBS
		37000 LBS
		38000 LBS 39000 LBS
		40000 LBS
		4000 LBS 41000 LBS
		42000 LBS
		43000 LBS
		44000 LBS
		45000 LBS
		46000 LBS
		48000 LBS

#### VOCATION

APPLICATIONS BODY CAPACITY CONCRETE PUMPER, ASPHALT DISTRIBUTOR, SWEEPER, ROAD PATCHER, REFUSE, CITY DELIVERY/BOX TRUCK, PAINT STRIPER, GEN UTILITY, GRINDER, ETC 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 16, 17, 18, 20 YARD

CAB INSTRUMENTATION	CAB WARNING DEVICES
SPEEDOMETER	PARK BRAKE
TACHOMETER	HIGH BEAM
ENGINE OIL PRESSURE	TURN SIGNAL
COOLANT TEMPERATURE	LOW FUEL
TRANSMISSION OIL TEMPERATURE	LOW AIR
VOLTMETER	SEAT BELT
FUEL LEVEL	DPF
HOUR METER	HEST
DEFLEVEL	AIR RESTRICTION INDICATOR
PRIMARY (A) AIR PRESSURE	FILTER WITH WATER IN FUEL INDICATOR
SECONDARY (B) AIR PRESSURE	



#### Autocar Expert MY 2020 Medium Duty 4X2 Class 8 Standard and Optional Specifications

ODOMETER TRIPMETER

#### OPERATORS CONTROLS PARK BRAKE PUSH/PULL

PARK BRAKE PUSH/PULL HEADLAMPS TURN SIGNAL COLUMN MOUNTED BRAKE PEDAL ACCELERATOR PEDAL TRANSMISSION GEAR SELLECTOR PUSH BUTTON

#### **OPTIONAL EQUIPMENT**

FIRE EXTINGUISHER DRY TYPE ABC 5LB. CAP MTD. IN CAB TRIANGLE FLARE KIT IN CAB ADDITIONAL INSTRUMENTATION AUTO NEUTRAL EXHAUST BRAKE METHANE DETECTION SYSTEM BATTERY SHUTOFF SWITCH WITH EMERGENCY JUMPER STUDS PTO CONTROL SWITCH DAYTIME RUNNING LAMPS

# AUTOCAR ACMD $^{\circ}$



	Autocar Expert MY 2020 Medium Duty 6X4 Cl	
ENGINE AND EQUIPMENT	STANDARD	OPTIONAL
ENGINE ASSY	L9 '17 300HP / 2200RPM / 860 LB-FT, CUMMINS	L9 '17, 260 HP / 2200RPM / 720 FT-LB, CUMMINS
		L9 '17, 270 HP / 2200RPM / 800 FT-LB, CUMMINS
		L9 '17, 350 HP / 2200RPM / 1000 FT-LB, CUMMINS
		L9 '17, 350 Hi HP / 2200RPM / 1150 FT-LB, CUMMINS
		L9 '17 330HP / 2200RPM / 1000 LB-FT, CUMMINS
		L9N '18 250 HP @ 730 FT-LB
		L9N '18 260 HP @ 660 FT-LB
		L9N '18 300 HP @ 860 FT-LB
IUFFLER SYSTEM (DIESEL)	LH VERTICAL SMA	RH HORIZONTAL SMA
MUFFLER SYSTEM (GAS)		LH VERTICAL CATALYST
		RH HOR CATALYST
JREA DELIVERY SYSTEM	RH FRAME MTD 5 GAL. CAPACITY	LH FRAME MTD 5 GAL. CAPACITY
		LH FRAME MTD 10 GAL. CAPACITY
		RH FRAME MTD 10 GAL. CAPACITY
		NO DEF TANK PROVIDED
AIR CLEANER	13" ONE STAGE	13" ONE STAGE WITH SAFETY ELEMENT
RADIATOR	1000 SQ. IN. ALUMINUM	
RADIATOR SHELL/HOOD BEZEL	NO RADIATOR GUARD	RADIATOR GUARD
FAN & DRIVE-ENGINE	2-SPEED FAN	
COOLANT HOSES	SILICONE HOSES WITH STEEL TUBING	
RADIATOR COOLANT	EXTENDED LIFE COOLANT	
ENGINE BLOCK HEATER	NO ENGINE BLOCK HEATER PROVIDED	PHILLIPS 120V 1000 WATT
HEATER RECEPTICAL LOCATION-ENGINE	NO BLOCK HEATER RECEPT. PROVIDED	RECEPTACLE LOCATED AT CAB STEPS, RH SIDE
STARTING AID-GLOW PLUG	GRID HEATER	NO ELECTRIC STARTING AID PROVIDED
HEATER-ENGINE OIL PAN	NO OIL PAN HEATER PROVIDED	ZERO-START,120V-150W, OIL PAN HEATER
ENGINE IDLE SHUT DOWN	ENGINE IDLE SHUT DOWN ENABLED ( 5 MINUTES )	ENGINE IDLE SHUT DOWN DISABLED
BRAKE-ENGINE	NO ENGINE BRAKE PROVIDED	CUMMINS VGT EXHAUST BRAKE
EXHAUST PIPING	NO EXHAUST BLANKETS	EXHAUST BLANKETS
<b>FRANSMISSION AND EQUIPMENT</b>	STANDARD	OPTIONAL
TRANSMISSION AND EQUIPMENT	ALLISON 3000 SERIES,6-SPEED	ALLISON 3500 SERIES,6-SPEED
	6-SPEED	ALLISON 5500 SERIES,0-SFEED
FRANSMISSION GEARING		
FRANSMISSION CONTROLS	ALLISON PUSHBUTTON CONTROLS	
COOLER-TRANSMISSION OIL	REMOTE MOUNTED TOC	
FRANSMISSION LUBRICANT	TRANSYND SYNTHETIC AUTO TRANS FLUID	
DRIVESHAFT-MAIN	SPICER 1710HD HALF ROUND	
FRANSMISSION SUPPORTS	NO TRANSMISSION SUPPORTS PROVIDED	TRANSMISSION REAR SUPPORT
TO-TRANSMISSION MOUNTED	NO TRANSMISSION MOUNTED PTO PROVIDED	PTO PREP - 3000/3500 TRANSMISSION W/ REAR SUPPORT
		MUNCIE CS6B-A6705-S1SS
		MUNCIE CS24-A1010-H3BX
RANSMISSION BREATHER	NO REMOTE TRANSMISSION BREATHER	TRANSMISSION REMOTE BREATHER
FRANSMISSION OIL FILL/CHECK	OIL FILL TUBE / DIPSTICK W/ LEVEL SENSOR	OIL FILL TUBE / DIPSTICK W / LEVEL SENSOR W / REMOTE BREATHER
		OPTIONAL
FRONT AXLE AND EOUIPMENT	STANDARD	
	STANDARD DANA 1202W STEER AXLE, 12000 LB CAPACITY	
	STANDARD DANA 1202W STEER AXLE, 12000 LB CAPACITY	DANA E-1322-W, 13,200 LB CAPACITY
		DANA E-1322-W, 13,200 LB CAPACITY DANA E-1462W STEER AXLE, 14600 LB CAPACITY
		DANA E-1322-W, 13,200 LB CAPACITY DANA E-1462W STEER AXLE, 14600 LB CAPACITY MERITOR MFS-14 STEER AXLE, 14700# RATING XXXX
		DANA E-1322-W, 13,200 LB CAPACITY DANA E-1462W STEER AXLE, 14600 LB CAPACITY MERITOR MFS-14 STEER AXLE, 14700# RATING XXXX MERITOR MFS-16 STEER AXLE, 16000# RATING
RONT AXLE	DANA 1202W STEER AXLE, 12000 LB CAPACITY	DANA E-1322-W, 13,200 LB CAPACITY DANA E-1462W STEER AXLE, 14600 LB CAPACITY MERITOR MFS-14 STEER AXLE, 14700# RATING XXXX MERITOR MFS-16 STEER AXLE, 16000# RATING MERITOR MFS-18 STEER AXLE, 18000# RATING
RONT AXLE		DANA E-1322-W, 13,200 LB CAPACITY DANA E-1462W STEER AXLE, 14600 LB CAPACITY MERITOR MFS-14 STEER AXLE, 14700# RATING XXXX MERITOR MFS-16 STEER AXLE, 16000# RATING MERITOR MFS-18 STEER AXLE, 18000# RATING 6000 LB FLATLEAF 13,200K GND CAP
RONT AXLE	DANA 1202W STEER AXLE, 12000 LB CAPACITY	DANA E-1322-W, 13,200 LB CAPACITY DANA E-1462W STEER AXLE, 14600 LB CAPACITY MERITOR MFS-14 STEER AXLE, 14700# RATING XXXX MERITOR MFS-16 STEER AXLE, 16000# RATING MERITOR MFS-18 STEER AXLE, 18000# RATING 6000 LB FLATLEAF 13,200K GND CAP 6500 LB FLATLEAF 14,500 GROUND CAPACITY
RONT AXLE	DANA 1202W STEER AXLE, 12000 LB CAPACITY	DANA E-1322-W, 13,200 LB CAPACITY DANA E-1462W STEER AXLE, 14600 LB CAPACITY MERITOR MFS-14 STEER AXLE, 14700# RATING XXXX MERITOR MFS-16 STEER AXLE, 16000# RATING MERITOR MFS-18 STEER AXLE, 18000# RATING 6000 LB FLATLEAF 13,200K GND CAP 6500 LB FLATLEAF 14,500 GROUND CAPACITY 7500 LB FLATLEAF 16,500 GROUND CAPACITY
RONT AXLE	DANA 1202W STEER AXLE, 12000 LB CAPACITY 5500 LB FLATLEAF 12,500 GROUND CAPACITY	DANA E-1322-W, 13,200 LB CAPACITY DANA E-1462W STEER AXLE, 14600 LB CAPACITY MERITOR MFS-14 STEER AXLE, 14700# RATING XXXX MERITOR MFS-16 STEER AXLE, 16000# RATING MERITOR MFS-18 STEER AXLE, 18000# RATING 6000 LB FLATLEAF 13,200K GND CAP 6500 LB FLATLEAF 14,500 GROUND CAPACITY
RONT AXLE RONT SUSPENSION HOCK ABSORBERS-FRONT	DANA 1202W STEER AXLE, 12000 LB CAPACITY 5500 LB FLATLEAF 12,500 GROUND CAPACITY DOUBLE ACTING SINGLE - HEAVY DUTY	DANA E-1322-W, 13,200 LB CAPACITY DANA E-1462W STEER AXLE, 14600 LB CAPACITY MERITOR MFS-14 STEER AXLE, 14700# RATING XXXX MERITOR MFS-16 STEER AXLE, 16000# RATING MERITOR MFS-18 STEER AXLE, 18000# RATING 6000 LB FLATLEAF 13,200K GND CAP 6500 LB FLATLEAF 13,200K GNUND CAPACITY 7500 LB FLATLEAF 16,500 GROUND CAPACITY 8500 LB FLATLEAF 18,800 GROUND CAPACITY
FRONT AXLE FRONT SUSPENSION SHOCK ABSORBERS-FRONT	DANA 1202W STEER AXLE, 12000 LB CAPACITY 5500 LB FLATLEAF 12,500 GROUND CAPACITY	DANA E-1322-W, 13,200 LB CAPACITY DANA E-1462W STEER AXLE, 14600 LB CAPACITY MERITOR MFS-14 STEER AXLE, 14700# RATING XXXX MERITOR MFS-16 STEER AXLE, 16000# RATING MERITOR MFS-18 STEER AXLE, 18000# RATING 6000 LB FLATLEAF 13,200K GND CAP 6500 LB FLATLEAF 14,500 GROUND CAPACITY 7500 LB FLATLEAF 16,500 GROUND CAPACITY 8500 LB FLATLEAF 18,800 GROUND CAPACITY DUAL INTEGRAL POWER STEERING TAS65
FRONT AXLE AND EQUIPMENT FRONT AXLE FRONT SUSPENSION SHOCK ABSORBERS-FRONT STEERING GEAR	DANA 1202W STEER AXLE, 12000 LB CAPACITY 5500 LB FLATLEAF 12,500 GROUND CAPACITY DOUBLE ACTING SINGLE - HEAVY DUTY	DANA E-1322-W, 13,200 LB CAPACITY DANA E-1462W STEER AXLE, 14600 LB CAPACITY MERITOR MFS-14 STEER AXLE, 14700# RATING XXXX MERITOR MFS-16 STEER AXLE, 16000# RATING MERITOR MFS-18 STEER AXLE, 18000# RATING 6000 LB FLATLEAF 13,200K GND CAP 6500 LB FLATLEAF 13,200K GNUND CAPACITY 7500 LB FLATLEAF 16,500 GROUND CAPACITY 8500 LB FLATLEAF 18,800 GROUND CAPACITY



		All 130 9001 2000 Certified Co
	Autocar Expert MY 2020 Medium Duty 6X4 Class 8 S	Standard and Optional Specifications
		DUAL INTEGRAL POWER STEERING TAS85
		DUAL INTEGRAL POWER STEERING TAS65
POWER STEERING RESERVOIR	TWO QUART REMOTE MOUNTED	FOUR QUART REMOTE MOUNTED
BRAKE CONTROL SYSTEM	ABS 6S/4M W/PLC	ABS 6S/4M W/ATC & PLC
BRAKES-FOUNDATION, FRONT AXLE	MERITOR 16.5X6 QP	
BRAKE DRUM-FRONT	CAST IRON	
BRAKE SLACK ADJUSTERS-FRONT AXLE	MERITOR AUTOMATIC	
HUBS-FRONT	STEEL HUB PILOTED,285MM BOLT CIRCLE	
HUB CAPS - FRONT AXLE	CR ZYTEL HUBCAP	
FRONT AXLE LUBRICANT	STANDARD	SYNTHETIC, DANA SPICER EP75W90, OR EQUIV
DUST SHIELDS - FRT BRAKES	NO FRONT BRAKE DUST SHIELDS PROVIDED	DUST SHIELDS - FRONT BRAKES
REAR AXLE AND EQUIPMENT	STANDARD	OPTIONAL
AXLE MODEL (TANDEM)	MERITOR MT40-14X (40000 LBS) (6.14 : 1 or 4.63/4.88/5.29/5.86:1 RATIO)	MERITOR RT46-160 (46000 LBS) (6.14 : 1 or 4.63/4.88/5.29/5.86:1 RATIO)
REAR SUSPENSION	HENDRICKSON HMX-400 SUSP @ 54 AS	HENDRICKSON HAS 402, AIR RIDE, 40,000 LB CAPACITY
		HENDRICKSON PAX-EX-462, AIR RIDE @ 54, 46,000 LB CAP
		HENDRICKSON HMX-460 SUSP @ 54 AS
SHOCK ABSORBERS-REAR	4 SHOCK ABSORBERS HENDRICKSON SUSPENSION	
BRAKE CONTROL SYSTEM	ABS 6S/4M W/PLC	ABS 6S/4M W/ATC & PLC
BRAKES-FOUNDATION, REAR AXLE	MERITOR 16.5X6 QP	
BRAKE DRUMS	CAST IRON	
BRAKE SLACK ADJUSTERS-REAR AXLE	MERITOR AUTOMATIC, TANDEM AXLE	
HUBS-REAR	IRON HUB, HP 10 STUD	
REAR AXLE LUBRICANT	STANDARD	SYNTHETIC
REAR AXLE LUBE PUMP	NO LUBRICATION PUMP	DIFFERENTIAL PUMP - MERITOR
REAR DRIVE AXLE STOPS	REAR BUMPSTOPS REQUIRED	NO REAR BUMPSTOPS REQUIRED
REAR DRIVE AXLE ANTI-SPIN DEVICES	NO ANTI-SPIN DEVICES PROVIDED	TANDEM AXLE REAR CARRIER ONLY
		FOUR WHEEL LOCK
TORQUE RODS	LONGITUDINAL ONLY - RUBBER BUSHED	LONGITUDINAL & TRANSVERSE - RUBBER BUSHED
WHEEL OIL SEALS-REAR	SCOTSEAL PLUS XL	
DUST SHIELDS - REAR BRAKES	NO REAR AXLE DUST SHIELDS PROVIDED	DUST SHIELDS - REAR BRAKES
CHASSIS AND EQUIPMENT	STANDARD	OPTIONAL
WHEELBASE	165 INCHES	150, 153, 156, 159, 162, 168 INCHES
		171, 174, 177, 179, 180, 183, 186, 189, 192, 195, 198 INCHES
		201, 204, 207, 210, 213, 216, 219, 220, 222, 224 INCHES
		RANGE BY REQUEST
FRAME RAILS	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM	
FRAME REINFORCEMENT INNER	.25" LINER, STANDARD LENGTH	
FRAME FASTENERS	HUCK BOLTS	FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING
BUMPER FRONT	STANDARD DUTY BUMPER	HEAVY DUTY
TOW DEVICE(S)	TWO TOW HOOKS INTEGRAL W/X-MEMBER	
FRAME-FRONT EXTENSION	NO FRONT FRAME EXTENSION PROVIDED	HD FRONT MOUTING EQUIPMENT (LOAD CAP 4000NM, 2950 TO 3800NM, 2800 FT. LBS.)
FRAME-REAR CUT-OFF	STRAIGHT	NOTCH FOR SWEEPER BODY
FRAME CROSSMEMBER-CENTER	7-PIECE STEEL CROSSMEMBERS	
FRAME CROSSMEMBER-OVERHANG	7 PC STEEL CMBR ROS - IF REQUIRED	
FRAME CROSSMEMBER-END CLOSING	NO FRAME END CLOSING X-MEMBER PROVIDED	STEEL
AIR TANK MOUNTING	AS MANY TANKS IN RAIL AS POSSIBLE	
PNEUMATIC SYSTEM (RAPID FILL)	STANDARD	OPTIONAL
AIR COMPRESSOR	CUMMINS WABCO 18.7 CFM COMPRESSOR	
AIR RESERVOIR DRAIN SYSTEM	PULL CORDS ALL TANKS	PULL CORDS WITH DV/2 WET TANK DRAIN
		PULL CORDS WITH HEATED DV/2 WET TANK DRAIN
		CENTRAL DRAIN MANIFOLD WITH DV/2 WET TANK DRAIN
		CENTRAL DRAIN MANIFOLD WITH HEATED DV/2 WET TANK DRAIN
		DV/2 IN ALL TANKS (NON HEATED)

DV/2 IN ALL TANKS (NON-HEATED)

CENTRAL DRAIN MANIFOLD W/HTD DV/2 WET TANK DRAIN/SCHRADER CHARGE PORT



Autocar Expert MY 2020 Medium Duty 6X4 Class 8 Standard and Optional Specifications STEEL AIR TANKS AIR TANK-BRAKE SAE J844 NYLON TUBING AIR LINES-MAIN, CHASSIS AIR DRYER WABCO 1200 PLUS AIR DRYER WABCO 1200 PLUS AIR DRYER W/HALDEX CONSEP CONDENSER/SEPARATOR EMERGENCY AIR SYSTEM CHARGING NO EMERGENCY CHARGING SYSTEM SINGLE GLADHAND, FRONT BUMPER, WET TANK STANDARD OPTIONAL FUEL SYSTEM FUEL TANK-LEFT TEMP. FUEL TANK 50 GAL RECT STEEL TANK, LH MOUNTED 50 GAL ALUMINUM RECR TANK, LH MOUNTED 75 GAL 26" DIA UNPAINTED ALUMINUM 75 GAL 26" ROUND STEEL TANK 100 GAL 26" DIA UNPAINTED ALUM 100 GAL 26" DIA STEEL ALTERNATE FUEL ENGINE-NO LH TANK DELETE LHS FUEL TANK FUEL TANK-RIGHT 50 GAL RECT STEEL TANK, RH MOUNTED DELETE RHS FUEL TANK 50 GAL ALUMINUM RECT TANK, RH MOUNTED 75 GAL 26" DIA UNPAINTED ALUMINUM 75 GAL 26" DIA STEEL 100 GAL 26" DIA UNPAINTED ALUM 100 GAL 26" DIA STEEL FUEL TANK MTD LHS OTHER THAN STD - SPECIFY FUEL TANK MOUNTING LHS FUEL TANK MTD FWD LHS - STD (IF PROVIDED) NO LH FUEL TANK POSITION FUELTANK MOUNTING RHS NO RH FUEL TANK POSITION FUEL TANK MTD FWD RHS - STD (IF PROVIDED) FUEL TANK MOUNTED RHS OTHER THAN STD - SPECIFY FUEL FILTER ENGINE MOUNTED SPIN-ON, ENGINE MOUNTED NATURAL GAS FUEL CLEANER FLEETGUARD FS SERIES F / W HEATER, SEPARATOR, PROBE & DASH LIGHT FUEL FILTER CHASSIS MOUNTED FLEETGUARD FS SERIES F / W SEPARATOR, PROBE & DASH LIGHT NO ADDITIONAL FUEL FILTER PROVIDED FUEL LINES SAE J844 NYLON TUBING STAINLESS STEEL FOR CNG OR LNG **OPTIONAL** TIRES AND WHEELS STANDARD TIRE SIZE & LOAD RANGE - FRONT 11R22.5G 12R22.5J 11R22.5H 12R22.5H 275/70R22.5J 295/75R22.5G 315/80R22.5L 315/80R22.5M WHEELS-DISC FRONT 22.5x8.25 STEEL HP, 6.18 INSET, 5HH 22.5x8.25 ALUMINUM HP, 5.79 INSET, ALCOA #883677 LV1 FINISH 22.5 x 8.25, ALUMINUM HP, 5.71 INSET, ACCURIDE 22.5X9.00 ALUMINUM HP, 5.96 INSET, ALCOA #89U64 22.5X9.00 ALUMINUM HP, 6.02 INSET, ACCURIDE (WEIGHT REDUCTION) 22.5x9.0 STEEL HP. 6.38 INSET. 5HH 22.5X9.0 STEEL, HP, 5.25 INSET, 5HH, ACCURIDE #29039 TIRE SIZE & LOAD RANGE - REAR 11R22.5G 11R22.5H 12R22.5H 12R22.5J 275/70R22.5J

WHEELS-DISC REAR

ELECTRICAL SYSTEM

ELECTRICAL SYSTEM

STANDARD 12V, NEGATIVE GROUND

22.5X8.25 STEEL, HP, 5HH

OPTIONAL

295/75R22.5G 315/80R22.5L 315/80R22.5M 455/55R22.5M

22.5X9.0 STEEL, HP, 5HH

22.5X8.25 ALUMINUM HP, ALCOA #883677 LV1 FINISH 22.5X14 ALUMINUM HP, ALCOA #840608 LV1 FINISH

22.5 x 8.25, ALUMINUM HP, ACCURIDE



		An ISO 9001:2000 Certified Company
	Autocar Expert MY 2020 Medium Duty 6X4 Class 8 Star	ndard and Optional Specifications
LTERNATOR	DELCO REMY 12V 130AMP 22SI	DELCO REMY 36SI 12V 160 AMP
		DELCO REMY 160 AMP, 28SI PAD MTD W/REMOTE SENSE
		DELCO REMY 200 AMP, 28SI PAD MTD.
TARTING MOTOR	DELCO REMY 12V 39 MT W/OCP	
ATTERY	2 BATTERIES, 31 ECL, 12V, 1900CCA	2 BATTERIES, 31 ECL, 12V, 2000CCA
ATTERY BOX	BATTERY BOX, 2 BATTERY CAPACITY	
ATTERY SHUT-OFF SWITCH	NO BATTERY SHUT-OFF SWITCH PROVIDED	SHUTOFF W/ LOCKOUT & EMERGENCY JUMPER STUDS
/IRING, BODY INTERFACE	NO BODY INTERFACE OPTION	RP 170 COMPLIANT
ACKUP ALARM	ECCO SMART ALARM SA917	ECCO RMS 917 WITH MOTION DETECTOR XXXX
		NO BACKUP ALARM PROVIDED
/INDSHIELD WIPERS	ELECTRIC INTERMITTENT WIPERS	
ORN	SINGLE ELECTRIC	
ORN-AIR	NO AIR HORN PROVIDED	TWIN MOUNTED UNDER CAB
IGHTING	STANDARD	OPTIONAL
AMPS-HEAD	RECTANGULAR SEALED BEAM	LED HEADLAMPS
AMPS-RUNNING	NO DAYTIME RUNNING LIGHTS PROVIDED	DAYTIME
AMPS-STOP-TAIL	NO TAIL OR BACK-UP LAMPS PROVIDED	DOT 4 INCANDESCENT TAIL (TURN/BRAKE/BACK-UP) LAMPS
		DOT 4 LED TAIL (TURN/BRAKE/BACK-UP) LAMPS
		DUAL LED TRUCKLITE MODEL 44
TOP-TAIL HARNESS	OMIT TAIL LAMPS, BB CONN @ EOF	STD TAIL LAMP WIRING
AMPS-TURN SIGNAL -FRONT	AMBER FRONT TURN SIGNALS	LED FRONT TURN SIGNALS
AMPS-MARKER	AMBER LED ROOF MARKERS	CLEARANCE (ROOF CORNER) LAMPS WIRED TO BATTERY SHUT OFF
		(LINK TO DISCONNECT SWITCH)
AB AND EQUIPMENT AB SHELL	STANDARD SINGLE LEFT HAND DRIVE CAB	OPTIONAL DUAL DRIVE LH AND RH SIT
AB SHELL	SINGLE LEFT HAND DRIVE CAB	SINGLE RIGHT HAND DRIVE CAB
AB DOORS	STEEL DOORS W/DUAL POWER WINDOWS	SIVOLE ROTTI HAVE DRIVE CAD
TEP-CAB ACCESS, CAB MOUNTED	DUAL SELF CLEANING CAB ENTRANCE STEPS	
AB FLOOR	WEAR RESISTANT MAT WITH FOAM BACK	
AB DASH	DARK GREY WRAP-AROUND, 2X OVERSIZED CUP HOLDERS	
VERHEAD CONSOLE	2X STORAGE BINS, CENTER MOUNTED RADIO SLEEVE	
AB MOUNTING	PROGRESSIVE RUBBER MOUNTS - FRONT COIL AND SHOCK ABS - REAR	
AB TILT MECHANISM-C.O.E.	HYDRAULIC TILT WITH OUTO ENGAGE SAFETY LATCH	
IIRRORS-DUAL WEST COAST	MIRROR, BLACK, MOTORIZED/HTD POLYCARBONATE HOUSING W/SQUARE	
	MOTORIZED/HTD CONVEX MIRROR	MIRROR, CHROME, HTD, REMOTE, W / LWR HTD CONVEX
IIRRORS-AUXILIARY	NO CONVEX AUX. MIRRORS PROVIDED	LOW MOUNT 8 CONVEX MIRROR BLACK POLYCARBONATE HOUSING
		HIGH MOUNT 8 CONVEX, CHROME
OWN VIEW MIRRORS	NO DOWN VIEW MIRRORS PROVIDED	SINGLE DOWN VIEW MIRROR, RH SIDE
		DUAL DOWN VIEW MIRRORS, ONE EACH SIDE
RILLE	AUTOCAR GRILLE BLACK	CHROMED AUTOCAR GRILLE
		AUTOCAR GRILLE WITH REMOVABLE WINTERFRONT COVER
		AUTOCAR CHROME GRILLE WITH REMOVABLE WINTERFRONT COVER
AB CLIMATE CONTROL SYSTEM	44,000 BTU FRESH AIR, HEATER AND AIR CONDITIONER, DIGITAL CLIMATE	
	201 MBR 07	
TEERING COLUMN	CONTROL	
	CONTROL ADJ. TILT AND TELESCOPIC STEERING COLUMN	DUAL ADJ. TILT AND TELESCOPIC STEERING COLUMNS
TEERING WHEEL		DUAL ADJ. TILT AND TELESCOPIC STEERING COLUMNS SINGLE DRIVE 18 INCH DIAMETER
	ADJ. TILT AND TELESCOPIC STEERING COLUMN	
	ADJ. TILT AND TELESCOPIC STEERING COLUMN	SINGLE DRIVE 18 INCH DIAMETER
	ADJ. TILT AND TELESCOPIC STEERING COLUMN	SINGLE DRIVE 18 INCH DIAMETER DUAL DRIVE 16 INCH DIAMETER DUAL DRIVE 18 INCH DIAMETER
TEERING WHEEL	ADJ. TILT AND TELESCOPIC STEERING COLUMN SINGLE DRIVE 16 INCH DIAMETER	SINGLE DRIVE 18 INCH DIAMETER DUAL DRIVE 16 INCH DIAMETER DUAL DRIVE 18 INCH DIAMETER ISRI HT914 HIGH BACK, AIR RIDE W/ RH ARM REST AND LUMBAR
TEERING WHEEL	ADJ. TILT AND TELESCOPIC STEERING COLUMN SINGLE DRIVE 16 INCH DIAMETER	SINGLE DRIVE 18 INCH DIAMETER DUAL DRIVE 16 INCH DIAMETER DUAL DRIVE 18 INCH DIAMETER
TEERING WHEEL EAT-DRIVER	ADJ. TILT AND TELESCOPIC STEERING COLUMN SINGLE DRIVE 16 INCH DIAMETER STANDARD MECHANICAL SUSPENSION WITH ADJ. DAMPENER	SINGLE DRIVE 18 INCH DIAMETER DUAL DRIVE 16 INCH DIAMETER DUAL DRIVE 16 INCH DIAMETER ISRI HT914 HIGH BACK, AIR RIDE W/ RH ARM REST AND LUMBAR SEARS SEAT W/ AIR RIDE SUSP, W/ AIR CONTROLLED LUMBAR SUPPORT ISRI HT914 HIGH BACK, AIR RIDE W/ LH ARM REST AND LUMBAR
FEERING WHEEL EAT-DRIVER EAT-PASSENGER	ADJ. TILT AND TELESCOPIC STEERING COLUMN SINGLE DRIVE 16 INCH DIAMETER STANDARD MECHANICAL SUSPENSION WITH ADJ. DAMPENER STANDARD MECHANICAL SUSPENSION SEAT WITH ADJ. DAMPENER	SINGLE DRIVE 18 INCH DIAMETER DUAL DRIVE 16 INCH DIAMETER DUAL DRIVE 16 INCH DIAMETER ISRI HT914 HIGH BACK, AIR RIDE W/ RH ARM REST AND LUMBAR SEARS SEAT W/ AIR RIDE SUSP, W/ AIR CONTROLLED LUMBAR SUPPORT ISRI HT914 HIGH BACK, AIR RIDE W/ LH ARM REST AND LUMBAR SEARS SEAT W/ AIR RIDE SUSP, W/ AIR CONTROLLED LUMBAR SUPPORT
TEERING WHEEL EAT-DRIVER EAT-PASSENGER DDITIONAL SEAT - PASSENGER	ADJ. TILT AND TELESCOPIC STEERING COLUMN SINGLE DRIVE 16 INCH DIAMETER STANDARD MECHANICAL SUSPENSION WITH ADJ. DAMPENER STANDARD MECHANICAL SUSPENSION SEAT WITH ADJ. DAMPENER NO THIRD MAN SEAT AND LAP BELT PROVIDED	SINGLE DRIVE 18 INCH DIAMETER DUAL DRIVE 16 INCH DIAMETER DUAL DRIVE 16 INCH DIAMETER ISRI HT914 HIGH BACK, AIR RIDE W/ RH ARM REST AND LUMBAR SEARS SEAT W/ AIR RIDE SUSP, W/ AIR CONTROLLED LUMBAR SUPPORT ISRI HT914 HIGH BACK, AIR RIDE W/ LH ARM REST AND LUMBAR
TEERING WHEEL EAT-DRIVER EAT-PASSENGER	ADJ. TILT AND TELESCOPIC STEERING COLUMN SINGLE DRIVE 16 INCH DIAMETER STANDARD MECHANICAL SUSPENSION WITH ADJ. DAMPENER STANDARD MECHANICAL SUSPENSION SEAT WITH ADJ. DAMPENER	SINGLE DRIVE 18 INCH DIAMETER DUAL DRIVE 16 INCH DIAMETER DUAL DRIVE 16 INCH DIAMETER ISRI HT914 HIGH BACK, AIR RIDE W/ RH ARM REST AND LUMBAR SEARS SEAT W/ AIR RIDE SUSP, W/ AIR CONTROLLED LUMBAR SUPPORT ISRI HT914 HIGH BACK, AIR RIDE W/ LH ARM REST AND LUMBAR SEARS SEAT W/ AIR RIDE SUSP, W/ AIR CONTROLLED LUMBAR SUPPORT

GVWR

52000 LBS



	Autocar Expert MY 2020 Medium Duty 6X4 Class 8 S	tandard and Optional Specifications
UN VISORS	LEFT AND RIGHT SIDE	
RADIO	RADIO PREP IN OVERHEAD CONSOLE	AM/FM / CD STEREO, ROOF MTD
		AM/FM/WB/MP3/CD/USB/BLUETOOTH
POWER PORT	12V AND DASH MOUNTED CIGAR LIGHTER	
ADDITIONAL ELEC. SWITCHES	NO ADDITIONAL ELEC. SWITCHES	2 DASH SWITCHES, WIRED TO POWER
		(2) DASH SWITCHES, (1) WIRED TO POWER FOR ROOF BEACON LIGHT
3RAKE VALVE & PEDAL	FIREWALL MTD LH BRAKE PEDAL FOR LHD	FIREWALL MTD RH BRAKE PEDAL FOR RHD
		FIREWALL MTD LHS, FLOOR MTD RH FOR DUAL DRIVE
PTO CONTROLS	NO TRANSMISSION PTO CONTROLS PROVIDED	PTO ELECTRIC CONTROL SWITCH
LAMPS-CAB INTERIOR	LED DOME LAMPS	FLEX MAP
KEY & LOCK SETS-IGN/DOORS	2 ADDITIONAL KEYS PER TRUCK (4 TOTAL)	4 ADDITIONAL KEYS PER TRUCK (6 TOTAL)
ler a look berb for books		KEYED ALIKE FLEET SET #1 (23112213)
DRIVER MONITORING SYSTEM	NO DRIVER CAM WIRING PREP OVERHEAD CONSOLE	DRIVER CAM WIRING PREP OVERHEAD CONSOLE
CAMERAS	NO CAMERAS OR PREP PROVIDED	3RD EYE CAMERA PREP (CAB ONLY)
	NO ELECTRONIC CONTROL MODULE	DIAGNOSTIC AND INFORMATION DISPLAY
TRUCK ELECTRICAL CONTROL MODULE		
VEHICLE MONITORING SYSTEM	NO GEOTAB TRUCK MONITOR OR PREP	GEOTAB TRUCK MONITOR PREP
		GEOTAB TRUCK MONITOR
PAINT	STANDARD	OPTIONAL
CAB PAINT TYPE	STANDARD WHITE	CAB FIRST COLOR OTHER THAN STD, NON METALLIC
		CAB FIRST COLOR, METALLIC
CHASSIS COLOR	BLACK P3036	CHASSIS COLOR OTHER THAN STD SPECIFY
BUMPER COLOR	BUMPER COLOR SAME AS CAB WHITE	PAINT SAME AS CAB, STEEL
		BUMPER COLOR SAME AS CHASSIS
DISC WHEEL OR RIM COLOR	STEEL, E-COAT WHITE / ALUM-UNPAINTED	CUSTOM COLOR - SPECIFY (PRICE PER WHEEL)
DISC WHELE OK KIM COLOK	STELL, E COM WHITE / MEON ON MICHED	STEEL, E-COAT GREY/ ALUM-UNPAINTED
AXLE WHEELEND COLOR	SAME AS CHASSIS	
BASIC WARRANTIES (INDUSTRY BEST)	STANDARD	OPTIONAL
CHASSIS WARRANTY	STANDARD WARRANTY	EXT WARRANTY - 2 YEARS / 200K MILES
		EXT WARRANTY - 3 YEARS / 300K MILES
		EXT WARRANTY - 4 YEARS / 350K MILES
		EXT WARRANTY - 5 YEARS / 400K MILES
ENGINE WARRANTY	CUMMINS STANDARD WARRANTY (2 YRS -ISL, 3 YRS ISB)	2017 L9 HD1 3YRS/100K MILES EXTENDED WARRANTY PP1 MATRIX #231157
		2017 L9 HD1 3YRS/150K MILES EXTENDED WARRANTY PP1 MATRIX #231157
		2017 L9 HD1 4YRS/200K MILES EXTENDED WARRANTY PP1 MATRIX #231157
		2017 L9 HD1 5YRS/150K MILES EXTENDED WARRANTY PP1 MATRIX #231157
		2017 L9 HD1 5YRS/250K MILES EXTENDED WARRANTY PP1 MATRIX #231157
		2017 L9 HD1 5YRS/300K MILES EXTENDED WARRANTY PP1 MATRIX #231157
		2018 L9N GE1 5 YRS/150K MILES EXTENDED WARRANTY PP1 MATRIX #334196
		2018 L9N GE1 5 YRS/200K MILES EXTENDED WARRANTY PP1 MATRIX #334196
CUMMINS AFTERTREATMENT	NO EXTENDED AFTERTEATMENT WARRANTY (2 YRS -ISL, 3 YRS ISB)	2017 L9 AT3 AFTERTREATMENT 3YRS/100K MILES EXT WARRANTY MATRIX #231545
COMMINS AFTER I REATIVIENT	NO EATENDED AFTERTEATMENT WARRANTT (2 TRS-ESL, 5 TRS ESD)	2017 L9 AT3 AFTERTREATMENT 3YRS/150K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 3YRS/150K MILES EXT WARRANTY MATRIX #231545
		201719 AT3 AFTERTREATMENT $4$ YRS $/200$ K MII ES EYT WARRANTV MATDIV #221545
		2017 L9 AT3 AFTERTREATMENT 5YRS/150K MILES EXT WARRANTY MATRIX #231545
		2017 L9 AT3 AFTERTREATMENT 4YRS/200K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/150K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231545 2012 L0 AT2 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231545
TD A NICMICCION W/ A DD A NITY	ALLISON 2VD. WADDANTTY	2017 L9 AT3 AFTERTREATMENT 5YRS/150K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231545
RANSMISSION WARRANTY	ALLISON 3YR WARRANTY	2017 L9 AT3 AFTERTREATMENT 5YRS/150K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231545
	ALLISON 3YR WARRANTY STANDARD	2017 L9 AT3 AFTERTREATMENT 5YRS/150K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231545
VEHICLE RATINGS		2017 L9 AT3 AFTERTREATMENT 5YRS/150K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231545 ALLISON 5YR WARRANTY
VEHICLE RATINGS VEHICLE TARE WEIGHT, FRONT	STANDARD	2017 L9 AT3 AFTERTREATMENT 5YRS/150K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231545 ALLISON 5YR WARRANTY
VEHICLE RATINGS VEHICLE TARE WEIGHT, FRONT VEHICLE TARE WEIGHT, REAR	STANDARD 8,395 lbs.	2017 L9 AT3 AFTERTREATMENT 5YRS/150K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231545 ALLISON 5YR WARRANTY
V <mark>EHICLE RATINGS</mark> VEHICLE TARE WEIGHT, FRONT VEHICLE TARE WEIGHT, REAR	<b>STANDARD</b> 8,395 lbs. 4,343 lbs.	2017 L9 AT3 AFTERTREATMENT 5YRS/150K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231545 ALLISON 5YR WARRANTY OPTIONAL 13000 LBS
V <mark>EHICLE RATINGS</mark> VEHICLE TARE WEIGHT, FRONT VEHICLE TARE WEIGHT, REAR	<b>STANDARD</b> 8,395 lbs. 4,343 lbs.	2017 L9 AT3 AFTERTREATMENT 5YRS/150K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231545 ALLISON 5YR WARRANTY OPTIONAL 13000 LBS 14000 LBS
V <mark>EHICLE RATINGS</mark> VEHICLE TARE WEIGHT, FRONT VEHICLE TARE WEIGHT, REAR	<b>STANDARD</b> 8,395 lbs. 4,343 lbs.	2017 L9 AT3 AFTERTREATMENT 5YRS/150K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231545 ALLISON 5YR WARRANTY OPTIONAL 13000 LBS 14000 LBS 16000 LBS
IRANSMISSION WARRANTY <b>VEHICLE RATINGS</b> VEHICLE TARE WEIGHT, FRONT VEHICLE TARE WEIGHT, REAR GAWF GAWR	<b>STANDARD</b> 8,395 lbs. 4,343 lbs.	2017 L9 AT3 AFTERTREATMENT 5YRS/150K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231545 2017 L9 AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231545 ALLISON 5YR WARRANTY OPTIONAL 13000 LBS 14000 LBS

53000 LBS



Autocar Expert MY 2020 Medium Duty 6X4 Class 8 Standard and Optional Specifications
54000 LBS
56000 LBS
58000 LBS
59000 LBS
60000 LBS

62000 LBS

DAYTIME RUNNING LAMPS

#### VOCATION

APPLICATIONS BODY CAPACITY CONCRETE PUMPER, ASPHALT DISTRIBUTOR, SWEEPER, ROAD PATCHER, REFUSE, CITY DELIVERY/BOX TRUCK, PAINT STRIPER, GEN UTILITY, ETC 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 16, 17, 18, 20, 22, 24, 25 YARD

CAB INSTRUMENTATION	CAB WARNING DEVICES
SPEEDOMETER	PARK BRAKE
TACHOMETER	HIGH BEAM
ENGINE OIL PRESSURE	TURN SIGNAL
COOLANT TEMPERATURE	LOW FUEL
TRANSMISSION OIL TEMPERATURE	LOW AIR
VOLTMETER	SEAT BELT
FUEL LEVEL	DPF
HOUR METER	HEST
DEF LEVEL	AIR RESTRICTION INDICATOR
PRIMARY (A) AIR PRESSURE	FILTER WITH WATER IN FUEL INDICATOR
SECONDARY (B) AIR PRESSURE	
ODOMETER	
TRIPMETER	

OPERATORS CONTROLS	OPTIONAL EQUIPMENT
PARK BRAKE PUSH/PULL	FIRE EXTINGUISHER DRY TYPE ABC 5LB. CAP MTD. IN CAB
HEADLAMPS	TRIANGLE FLARE KIT IN CAB
TURN SIGNAL COLUMN MOUNTED	ADDITIONAL INSTRUMENTATION
BRAKE PEDAL	AUTO NEUTRAL
ACCELERATOR PEDAL	EXHAUST BRAKE
TRANSMISSION GEAR SELLECTOR PUSH BUTTON	METHANE DETECTION SYSTEM
	BATTERY SHUTOFF SWITCH WITH EMERGENCY JUMPER STUDS
	PTO CONTROL SWITCH